

CS Series CST20

A complete acoustic upgrade in a single box, the ¾-inch titanium-dome tweeters are optimized to fit any vehicle with a flush, surface and angled mounting kit included. Getting a custom look to go with your custom sound has never been easier.

These tweeters work best with 50 watts of recommended power. See below for more details.

- Fits nearly every car made
- Titanium tweeter construction and neodymium magnets reveal subtle details
- 6dB in-line crossovers for tweaking the most perfect frequencies
- Built-in poly-switch protection for higher volumes
- Three tweeter mounting options including flush, angled and surface

Specifications

Tweeter [in,mm]
3/4, 20

Dome Material
Titanium

Rated Impedance [Ω]
4

Peak Power (watts, per ANSI/CTA-2031-A)
100

Recommended Amplifier Power (watts RMS)
50

Sensitivity [1W, 1m]
92

Frequency Response [Hz]
4,500-21k

Flush Mount Tweeter Depth [in, mm]
9/16, 14.5

Flush Mount Tweeter Hole Diameter [in,mm]
1-9/16, 40

High Pass [dB], at Frequency [Hz]
6, 4500

Support

Manuals

2019 CS Tweeters | Multilingual | Download (/app/manuals/mids_tweets/cs/2019_CS_Tweeter.pdf)

Do you have a different model? Click Here (/product-manuals)

Support Links