

UTTERMOST

ASSEMBLY INSTRUCTIONS

22552

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF WHILE POWER BEFORE INSTALLING OR SERVICING THIS FIXTURE.

We suggest a licensed professional electrician for installation

Installation Steps

1. Turn power off at fuse or circuit box before starting installation process.
2. Carefully unpack your new fixture and lay out all the parts on a clear surface.
3. Thread the Mounting screws into the matching holes of the Circular strap, and tighten with the Hex nut. Thread the Ground screw into the hole of the Circular strap. Secure the Circular strap to the outlet box with the Outlet box screws.
4. Make Wire connections with Wire Connector:
 - The smooth wire (w/ marking) from fixture to Black Wire from power source.
 - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
 - Attach the Ground Wire and house ground wire to the Mounting bar with the green Ground screw.Carefully tuck wires back into the Outlet Box.
5. Place the fixture Back plate over the two Mounting screws so they protrude through the holes in the Back plate. Thread the Ball nut onto the Mounting screws and continue turning until the fixture is snug against the wall.
6. Slide the Glass over the Socket, then secure with the Socket ring.
7. Install the light bulb (Not Supplied) in accordance with the fixture's specifications.
8. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**

