

## High-fidelity. Low profile.

Leon's Profile™ Series speakers are hand-crafted and built-to-order to match the **exact height and finish of any flat-panel display**. Available as multi-channel or stereo speakers, the Profile Series provides a powerful, high-fidelity two channel or Living Space home theater experience. At less than 2" deep, the Profile Ultra-Thin Series perfectly complements the slim new LCD and LED TVs from manufacturers like Samsung®, Panasonic® and LG®. Each Profile Ultra-Thin speaker features state-of-the-art woofers and cloth-dome tweeters, creating truly astounding high-fidelity sound from a cabinet that is as thin as the TV itself.

Custom built to match the **exact height and finish of any display**

Ultra-thin designs work perfectly with even the thinnest TVs

Multi-channel option available for LCR or distributed audio applications

Easily mounts to any articulating TV with Leon's exclusive brackets

Also available as freestanding towers



PrUT shown above without grill ▲

### PR202-UT

Recommended for Ultra-Thin TVs less than 42". Cabinet dimensions: 3.25" wide x 1.5" deep (height matches size of TV)

Model ID	Driver Size and Description	Power	Ohms	Frequency	Sensitivity
<b>PR202-UT:</b>	<b>LR :</b> (4) 2" midrange woofer; (2) 1" cloth-dome tweeters	90w	8Ω	160-20kHz	88dB@1w/1m
	<b>+ :</b> (4) 2" midrange woofer; (2) 1" cloth-dome tweeters	90w	8Ω	160-20kHz	88dB@1w/1m

### NEW PRUT

Recommended for 42"-50" Ultra-Thin TVs. Cabinet dimensions: 4" wide x 1.5" deep (height matches size of TV)

Model ID	Driver Size and Description	Power	Ohms	Frequency	Sensitivity
<b>PRUT:</b>	<b>LR :</b> (4) 2.5" midrange woofer; (2) 22mm cloth-dome tweeters	65w	8Ω	120-20kHz	90dB@1w/1m
	<b>+ :</b> (2) 2.5" midrange woofer; (2) 22mm cloth-dome tweeters	65w	8Ω	120-20kHz	90dB@1w/1m

### NEW PRUT-X-A

Recommended for 50"-65" Ultra-Thin TVs. Cabinet dimensions: 4.5" wide x 1.875" deep (height matches size of TV)

Model ID	Driver Size and Description	Power	Ohms	Frequency	Sensitivity
<b>PRUT-X-A:</b>	<b>LR :</b> (4) 3" midrange woofer; (2) 1" audiophile-grade tweeters	80w	8Ω	80-20kHz	88dB@1w/1m
	<b>+ :</b> (2) 3" midrange woofer; (2) 1" audiophile-grade tweeters	80w	8Ω	80-20kHz	88dB@1w/1m

+ indicates the optional additional channel for distributed audio or LCR applications in multi-channel (-MC) speakers

