

GENERAL			
Number of Channels	2	Amplifier Class	Class AB
Maximum Power Output	1000W	Maximum Power Output at 2 ff	500W x 2
Maximum Power Output at 4 ff	300W x 2	Maximum Power Output - Bridged at 4 ff	1000W
Nominal Power (RMS) Output at 2 ff	240W x 2	Nominal Power (RMS) Output at 4 ff	150W x 2
Nominal Power (RMS) Output - Bridged at 4 ff	480W x 1	Frequency Response	10Hz ~ 70kHz (+0dB , -3dB)
Total Harmonic Distortion (THD)	<0.05% (10W, 1kHz)	Signal-to-Noise (SN) Ratio	> 96dB
Fuse Rating	30Ax2		

SPECIFICATIONS			
RCA Inputs	2-CH	Speaker Level Inputs	✔
Crossover Type	Adjustable LPF	Low-Pass Crossover Frequency	40-500 Hz
Low Pass Slope (dB/octave)	-12db/oct	Bass Boost Frequency	50Hz
Bass Boost Level	0/6/12dB	Automatic Signal Sensing and Turn-On	✔
Hi-Volt Input Level Control	0/6/12dB	Terminal Type	Screw
Load Impedance Allowance (Ω)	2 to 4	Bridgeable	✔
Protection Control System	✔	Dimensions (WxHxD)(inches)	356(W) X 60(H) X 215(D) mm
Warranty	1 Year		