Café[™] Energy Star[®] 22.2 Cu. Ft. Counter-Depth French-Door Refrigerator with Keurig[®] K-Cup[®] Brewing System



DISTINCT BY DESIGN™

CYE22UP2MS1



CYE22UP2MS1 Stainless Steel with Brushed Stainless handles



FEATURES & BENEFITS

Brew your favorite morning latte or cappuccino from a **Keurig K-Cup brewing system** built directly into the refrigerator.

Steep a relaxing herbal tea or prepare light & fluffy couscous with an adjustable **hot water dispenser** that provides precise temperatures and measurements.

Use your voice or **smart device** to preheat water from your refrigerator while you relax in another part of the house.

Create a built-in look with **counter-depth design** that fits flush with surrounding cabinetry.

Leave the measuring cups in the drawer with a **Precise Fill setting** that dispenses an exact amount of water with just a touch.

Food remains fresh longer with **TwinChill™ evaporators** that accurately maintain and control separate freezer and refrigerator environments.

Keep key ingredients fresh and within sight with a full-width, electronic, **temperature-controlled drawer** that uses an LED colored lighting system.

Display groceries like a gallery with **showcase LED lighting** positioned throughout the interior to spotlight your favorite foods and containers.

APPEARANCE

TH T MARCH (CD		
Counter-depth design	Yes	
Exterior design	Flat doors	
Handle design	GE Café	
Hidden door hinge(s)	Yes	
Textured steel case	Case only—Dark gray	

Configuration	French door	
WiFi connect	Built-in	
Connected capabilities	Amazon Alexa The Google Assistant	
Temperature management features	Turbo Cool setting	
Temperature management system	TwinChill [™] evaporators	
Defrost type	Frost Guard	
Control type	External touch color LCD	
Dispenser	Large stainless steel cubes, crushed ice and water	
Dispenser features	Hot water Precise Fill LCD screen controls USB port for photo upload Door alarm LED dispenser light Water filter indicator light Single serve K-cup	
lcemaker	Space saving ice	
Water filtration	Advanced filtration system (RPWFE); Removes pharmaceuticals Water filter indicator light	
Filter location	Left wall	
Fresh food cabinet drawers	3 total 2 adjustable humidity drawers 1 full-width, adjustable temperature with LED light	
Fresh food cabinet shelves	5 total—glass with silver trim 4 split adjustable 1 full-width 3 spill proof 1 Quick Space shelf	
Fresh food door bins	6 total (4 stainless steel design) 2 adjustable 3 with gallon storage	
Fresh food door features	Dairy compartment Drop down tray	
Fresh food features	Showcase LED lighting (7); Deli pan	
Freezer door bins	1 tilt-out	
Freezer storage baskets	2 full-width	
Freezer features	Turbo Freeze; interior lighting—showcase LED (2)	
Exterior style	Counter-depth	
Leveling system	2 front leveling legs	
Performance features	Easily removable door gaskets; Sabbath Mode capable	

CAPACITY

Onnorr	
Total capacity (cubic feet)	22.2 cu. ft.
Fresh food capacity	15.0 cu. ft.
Freezer capacity	7.2 cu. ft.

WEIGHTS & DIMENSIONS

WEIGHTIG & DIMERIOIOTIG		
all depth 31-1/4 in.		
all height 69-7/8 in.		
all width 35-3/4 in.		
depth without door 24-3/8 in.		
with door open 90° 43-3/8 in.		
n without handle 29-3/4 in.		
t to top of case 69 in.		
with door open 90° ling handle 44-3/4 in.		
oximate shipping weight 398 lb.		
reight 365 lb.		
eight 305 lb.		

Café[™] Energy Star[®] 22.2 Cu. Ft. Counter-Depth French-Door Refrigerator with Keurig[®] K-Cup[®] Brewing System




CYE22UP2MS1

WARRANTY

Parts warranty	Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
Labor warranty	Limited 1-year entire appliance; Limited 5-year sealed refrigerating system
Warranty notes	See written warranty for full details

DIMENSIONS



Height to top of door (in.) A	70-1/2	
Height to top of hinge (in.) B	69-7/8	
Height to top of case (in.) C	69	
Case depth without door (in.) D**	24-3/8	
Case depth less door handle (in.) E**	29-3/4	
Case depth with door handle (in.) F**	31-1/4	
Depth with fresh food door open 90° (in.) G**	43-3/8	
Width (in.) H	35-3/4	
Width with door open 90° with door handle (in.) I	44-3/4	
Width with doors open fully (in.) J	61-5/8	
Min distance between side of case and wall, in either direction, to allow doors to open fully (in.) ${\bf K}$	13-1/8	
Depth with FZ door completely open (w/o handle) (in.) ${\bf X}$	44-1/4	
Depth with FZ door completely open (w/ handle) (in.) Y	46-3/4	
*Includes hot water knob. **Water hookup fits in back air clearance when calculating installation depth.		

ADDITIONAL ACCESSORIES



CXLB3H3PMBZ Brushed Bronze 3 handles (Standard on Matte White)



CXLB3H3PMSS Brushed Stainless 3 handles (Standard on Matte Black and Stainless Steel)



CXLB3H3PMBT Brushed Black 3 handles



10 1. T



CXMA3H3PNCG Brushed Brass 3 handles

CXLB3H3PMCU Brushed Copper 3 handles

CXMA3H3PNFB Flat Black 3 handles

3 handles

For answers to your Café[™] product questions, visit our website at cafeappliances.com.