

The sculpted lines of Alta™ bring an exciting, new choice to typical range hood shapes. Sophisticated curves and hidden controls offer a beautiful alternative to traditional designs.

SIZE	BLACK	STAINLESS	WHITE	GREASE FILTER(S) (replacement)	NON-DUCTED FILTER(S)
30-in.	BQSJ130BL	BQSJ130SS	BQSJ130WW	HPFAMM30 (Type "C1" / "C2")	HPF30 (Type "Xc")
36-in.	BQSJ136BL	BQSJ136SS	BQSJ136WW	HPFAMM36 (Type "D1" / "D2")	HPF36 (Type "Xd")

PERFORMANCE									
Donat Orientation	Size	Damper	Sones		CFM @ 0.1 Ps				
Duct Orientation			Normal	High	Normal	High			
Vertical - Rectangular	3¼-in. x 10-in.	Included	1.5	5.0	140	230			
Horizontal - Rectangular	3¼-in. x 10-in.	Included	1.5	5.0	110	210			
Round - Vertical	7-in.	Sold Separately	1.5	5.0	150	250			

FEATURES					
Control type	2-speed Rocker				
Delay off	no				
Filter Clean Reminder	no				
Heat Sentry™	no				
ADA Capable	yes				
Lighting	2-level Halogen (included)				
Grease Filter(s)	Micro Mesh (Qty. 2)				
Installation Hardware	EZ1 Bracket				
ENERGY STAR®	no				
Recirculation	Non-ducted filter(s) sold separately				
AC INPUT					
120V, 60 Hz - 1.4 AMPS					

OPTIONAL ACCESSORIES

7-in. Round Damper BP87


MOUNTING HEIGHT

18-in. to 24-in. from cooktop to bottom of hood


LIMITED WARRANTY

1-yea

FOR INDOOR USE ONLY









BQSJ1 SERIES

SPECIFICATION SHEET



HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.