


# PP7036EJ

## GE Profile™ Series 36" Built-In Knob Control Cooktop

### DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)

**IMPORTANT:** Requires a 5" free area between the bottom of the cooktop to any combustible material, i.e., shelving. Free area not required when installing wall oven underneath cooktop. Refer to installation instructions. Requires a 15" minimum from cooktop to adjacent overhead cabinets. Units are furnished with a 48" flexible armored cable.

**NOTE:** 36" Ribbon cooktops are approved for use over select GE 30" Single Wall Ovens and Warming Drawers. Refer to cooktop and wall oven/warming drawer installation instructions packed with product for current dimensional data. If installed with a GE Telescopic Downdraft System, consult both the cooktop and downdraft installation instructions packed with product before installing. Cooktop gas/electric supply may need to be re-routed to install downdraft. The countertop cutout requires 23-1/2" minimum flat countertop surface and 25" minimum total countertop depth. In addition, other clearances to front edge of the countertop must be considered. Before installing, consult installation instructions packed with product for current dimensional data.



To insure accuracy, it is best to make a template when cutting the opening in the counter

| KW Rating |                      |
|-----------|----------------------|
| 240V      | 9.6                  |
| 208V      | 8.3                  |
| Amperage  |                      |
| 240V      | 40 Amps <sup>†</sup> |
| 208V      | 40 Amps <sup>†</sup> |

**NOTE:** Check local codes for required breaker size



**GE APPLIANCES**

For answers to your Monogram,® GE Profile™ or GE® appliance questions, visit our website at [geappliances.com](http://geappliances.com) or call GE Answer Center® service, 800.626.2000.



Listed by  
Underwriters  
Laboratories


Specification Revised 5/15

# PP7036EJ

## *GE Profile™ Series 36" Built-In Knob Control Cooktop*

### **FEATURES AND BENEFITS**

- Five radiant cooking elements - Cook foods quickly and evenly on this sleek, glass surface
- 6"/9"/12" tri-ring element - Use different pan sizes on this single, 3,000-watt flexible element
- 5"/8" Power Boil element - Use different pan sizes on this single, 2,400-watt flexible element that produces rapid powerful heat
- SyncBurners - Control two 7" elements simultaneously to evenly heat large cookware or griddles\*
- Keep Warm setting - Keep food warm with GE's lowest heat setting or boil water in minutes with this fully functional 6" element
- Melt setting - Gently melt delicate foods without burning or scorching
- Control lock capability - Protects against unintended activation
- Red LED backlit knobs with patterned glass surface - Achieve a modern look with the convenience of knob controls
- Hot surface indicator lights - Know when elements are too hot to touch with a quick glance
- Cooktop "On" indicator light - A light lets you know when an element is active
- Model PP7036EJES - Slate



### **\*OPTIONAL STAINLESS STEEL CLAD ALUMINUM GRIDDLE**

Achieve even results with this lightweight griddle, tailored to fit GE SyncBurners. Order part number JXGRIDL1 from your GE Dealer.



### **GE APPLIANCES**

For answers to your Monogram®, GE Profile™ or GE® appliance questions, visit our website at [geappliances.com](http://geappliances.com) or call GE Answer Center® service, 800.626.2000.