



SO3050TM/S/T



FEATURES

Preheats faster and cooks more consistently across all racks due to its advanced Dual VertiFlow™ convection system

Assures predictably delicious results with a variety of modes, including Convection Roast, Proof, and Dehydrate

Prepares 50 popular dishes with the Gourmet feature that automatically adjusts cook times and temperatures

Handles multiple dishes simultaneously with our largest capacity oven (13 percent larger)

Insert a temperature probe to tell you exactly when it is done—and in Gourmet Mode, it will alert you the moment the dish is ready.

Uncomplicate cooking with innovative, interactive color touchscreen controls

Complements any kitchen with its design versatility

Integrates beautifully into surrounding cabinetry with flush installation

Ensures excellent visibility via three bright halogen lights and large, triple-panel-glass door windows

Master your technique with tips and recipes from the Mastering the M Series Oven guide

ACCESSORIES

30" Broiler Pan and Rack

30" Full-Extension Ball-Bearing Oven Rack

30" Multifunction Pan

30" Premier Baking Sheet

30" Standard Oven Rack

Bake Stone Kit

Dehydration Kit

Dual Installation Kit

Temperature Probe

Accessories available through an authorized dealer.
For local dealer information, visit subzero-wolf.com/locator.



DIMENSIONS

Technical drawings of the oven showing front and side views with dimensions in inches and millimeters.


Front View Dimensions:

- Overall Width: 29 7/8" (759)
- Overall Height: 28 1/2" (724)
- Top Panel Width: 7 1/8" (22)
- Top Panel Height: 8 5/8" (218)
- Side Panel Width: 2" (51)
- Side Panel Height: 13 3/8" (36)
- CONDUIT CHANNEL
- Bottom Panel Width: 23" (584)
- Bottom Panel Height: 27" (686)




Side View Dimensions:

- Overall Width: 28 1/2" (724)
- Overall Height: 21 3/8" (543)
- Top Panel Width: 17 1/8" (46)
- Bottom Panel Width: 21 3/8" (543)
- Bottom Panel Height: 21 3/8" (543)
- Bottom Panel Label: OPEN OVEN DOOR

FLUSH INSTALLATION



NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified



SIDE VIEW

FRONT VIEW

***1" (25) minimum depth. Shaded areas will be visible and should be finished to match cabinetry.**
****Dimension provides minimum reveals.**

NOTE: Location of electrical supply within opening may require additional cabinet depth.