



## Drying cabinet

DC7784V.G.U

### Vented

**Total drying length: 16 m**

**Installation: Freestanding**

**Graphite black**

### Construction

- Product type: Vented
- Door hinge placement: Right
- Color of the product: Graphite black
- Cabinet material: Stainless Steel
- Installation: Freestanding

### Standard electrical connection

- Heater power: 1500 W
- Voltage (V): 120 V
- Frequency: 60 Hz
- Length of electrical cord: 90 3/16 "
- Number of phases: 1

### Controls

- Remaining time indication: Yes

### Logistic information

- Packaging width: 25 9/16 "
- Packaging height: 74 13/16 "
- Packaging depth: 27 9/16 "
- Width: 23 7/16 "
- Height: 73 "
- Depth: 23 15/16 "
- Net weight: 138.9 lb
- Gross weight: 162.9 lb
- Reversible door hanger: Yes
- Possible to install in cabinet: Yes
- Possible to wall mounted: Yes
- Depth with door open: 46 5/16 "
- Ventilation hose length: 39 3/8 "
- Venting position / diameter: On top-diameter 100
- Product code: 746874

### Performance

- Timed drying: Yes
- Temperature selection: Yes
- Dewatering capacity (g/min): 17
- Total drying length: 16 m
- Shortest program time: 75 min

### Energy label information

- Noise level drying dB(A): 55

### Programs

- Drying programs: Auto 40 °C Normal Dry, Auto 40 °C Extra Dry, Auto 60 °C Normal Dry, Auto 60 °C Extra Dry, Manual 30 °C, Manual 40 °C, Manual 60 °C, Manual \_ \_

### Test certificate

- ISO 14001 certified manufacturing: Yes

**EAN**

- EAN code: 3838783025371

**Safety and maintenance**

- Safety door switch: Yes

