# Product data sheet

### **CONSTRUCTION TYPE**

Built-in appliance	•	
Integrated appliance	•	
Door hinging	Right convertible	
Convertible hinging	•	
Can be installed side by side	•	

### **DESIGN**

**Lighting** BrilliantLight

### **USER CONVENIENCE**

Freshness system	MasterFresh
DuplexCool Pro	•
FullAccess	•
EasyClean	•
MaxLoad hinge	•
IceMaker with fresh-water connection	•
DynaCool	•
NoFrost	•
NoFrost	•
SelfClose	•
Push2open	•

Networking with Miele@home	•
CONTROLS	
Eco mode	•
User interface	MasterSensor
Independent temperature regulation of fridge and freezer compartments	•
SuperCool	•
Number of temperature zones	3
Sabbath mode	•
Holiday mode	•
FRIDGE / FRIDGE SECTION	
SlidingShelf	•
Door rack for tins	1
Height-adjustable tempered glass shelves	1
Number of crisper drawers	2
Door rack for bottles	2
FREEZER / FREEZER SECTION	
Number of freezer baskets	2
EFFICIENCY AND SUSTAINABILITY	
Energy Star	•

Overflow protection	•
Safety lock	•
Acoustic door alarm	•
Acoustic temperature alarm, freezer section	•
Optical door alarm	•
Optical temperature alarm	•

## **TECHNICAL DATA**

Replacing lamps	Customer Service
Number of phases	1
Niche width in inches (mm), min.	30 (762)
Niche width in inches (mm), max.	30 (762)
Niche height in inches (mm), min.	84 1/8 (2134)
Niche height in inches (mm), max.	84 1/8 (2134)
Niche depth in mm	24 7/8 (629)
Appliance width in mm	29 7/8 (756)
Appliance height in mm	83 3/4 (2125)
Appliance depth in mm	24 (608)
Weight in lbs (kg)	389 (176.0)
Door hinge technology	Fixed door
Max. weight of door, fridge section, in kg	100 (45)
Max. weight of door, freezer section, in kg	40 (18)
Total usable capacity in I	15.96 (452) ft³ (I)
Current consumption in milliamps (mA)	4000
Voltage in V	110-120
Fuse rating in A	10
Frequency in Hz	60

10/19/23, 1:42 PM KF 2802 Vi | Miele

Length of power cable in m	11 (3.5)
ACCESSORIES SUPPLIED	
Active AirClean filter	•
APPLIANCE CATEGORY	
Fridge / freezer	•
AVAILABLE DISPLAY LANGUAGES	
Available display languages via Language Options	bahasa malaysia