## 30-Inch Drawer Microwave





DMR30M977WS - Silver Stainless \$1,899 DMR30M977WM - Graphite Stainless \$1,999

## Features & Benefits


- · Motorized drawer
- · 10 preset modes
- · Smart moisture sensor
- · Multi-sequence cooking
- · Automatic start
- Keep warm
- · Electronic control panel

Weights & Dimensions				
NET WEIGHT (LBS.)		105		
SHIPPING WEIGHT (LBS.)		89		
PRODUCT DIMENSIONS (W X H X D IN INCHES)		30 x 15 % x 23 1/4		
STANDARD CUTOUT REQ (W X H IN INCHES)	UIRED	22 ½ (min) to 28 ½ (max) x 15 ½ x 23 ½		
FLUSH CUTOUT REQUIRE (W X H IN INCHES)	D	30 % (min) to 30 % (max) x 16 % x 23 ½		
Technical Details				
ELECTRICAL REQUIREMENTS		120V, 60 Hz, 15A		
Warranty				
FULL COVERAGE		2 Years		
Controls				
CONTROL TYPE		Glass Touch		
СГОСК		Yes		
CHILD LOCK		Yes		
Microwave Oven				
MICROWAVE CAPACITY (CU. FT.)		1.2		
MICROWAVE POWER		950W		
SENSOR COOK		Yes		
CONVECTION		No		
LIGHTING		Halogen		
Accessories (Optional)				
ADMRF30S	Flush Installation Kit, Silver Stainless \$69		\$69	
ADMRF30M	Flush Installation Kit, Graphite Stainless \$79		\$79	

## 30-Inch Drawer Microwave



Product Dimensions			
A - ANTI-TIP BLOCK LENGTH (IN)	6		
B - ELECTRICAL OUTLET LOCATION (IN)	-		
C - ANTI-TIP BLOCK (IN)	_		
D - OUTLET LOCATION HEIGHT (IN)	5		
E - ANTI-TIP BLOCK WIDTH (IN)	3 ½		
F - OUTLET LOCATION WIDTH (IN)	4		
G - CUTOUT-OPENING WIDTH RANGE (IN)	22 ½ (min.) to 28 ½ (max.)		
H - CUTOUT FLOOR TO BLOCK BOTTOM (IN)	14 13/16		
I - MINIMUM OVERLAP ALLOWANCE, SIDES (IN)	23/32		
J - MINIMUM CUTOUT DEPTH (IN)	23 ½		
K - MINIMUM OVERLAP ALLOWANCE (IN)	3/16		
L - NOMINAL COUNTERTOP HEIGHT (IN)	36		
M - MINIMUM OVERLAP ALLOWANCE, BOTTOM (IN)	1/8		
N - MINIMUM CABINET WIDTH (IN)	30		
O - CUTOUT HEIGHT (IN)	15 %		



Product Dimensions		
A - OVERALL CHASSIS WIDTH (IN)	21 %	
B - WIDTH OF CHASSIS NOTCH (IN)	4 11/16	
C - HEIGHT OF CHASSIS NOTCH (IN)	1 3/4	
D - CHASSIS DEPTH (IN)	21 7/8	
E - MICROWAVE FACE WIDTH (IN)	30	
F - WITH MODERNIST HANDLE (IN)	15 7/8	
G - CHASSIS HEIGHT (IN)	14 1%32	
H - DOOR FACE THICKNESS (IN)	1 %4	
I - AUTOMATIC DRAWER-OPEN DEPTH (IN)	15	
J - CHASSIS NOTCH WIDTH (IN)	4	

