





This model provides professional grade performance, while being discreetly mounted inside the cabinetry. Available with a 600 CFM blower for extraordinary ventilating power. Plus the All-In-One design avoids the need to purchase a stainless liner. Hidden metallic in/out knob controls operate the 4-speed blower and LED lighting. A cleaner kitchen is ensured by angled professional baffle filters.

*Outdoor Rated Pro Style Hood.

MOUNTING
HEIGHT RANGE

$\frac{1}{2}$ " $\frac{1}{2}$ "
 $\geq 24"$ $\geq 30"$



SPECIFICATIONS

Width:	34" Unit
Model:	PINTR634SS
Dimensions:	34 1/2"W x 18"D x 11 7/8"H
Blower Type(internal):**	600 CFM(4-speed)
Noise (sones):**	1.7-7.0 Sones
Finish:	Stainless Steel
Controls:	Fully Retractable Rotating Knobs with White Backlighting
Illumination: (replaceable lamps 1 intensity)	2 LED, 6.5 Watts 3000 KELVIN 540 LUMEN/Lamp
Grease Filter:	(2) Grease Collecting Stainless Steel Baffle
Duct Transition:	6" Round with Backdraft Damper (top only)
Installation Type:	Ducted or Recirculating with Kit
Mounting Height Range:	Electric ≥ 24", Gas ≥ 30"
Electrical:	120V - 60 Hz, 490 Watts
ACCESSORIES: Inline Blower Shell Kit:	ACC0205342 (6" duct size compatible. For use with 600 CFM models)
Recirculating kits:	
Carbon filters:	ACC0192765 (Contains 4 round carbon filters)
Deflector:	ACC0195736 (6" round metal deflector for 600 CFM models)
WARRANTY:	Two (2) years parts & in-home labor

FEATURES



Quiet System - Specialized technology that allows reducing sound levels of your hood, which can effectively decrease noise by more than 35%.



Grease Collecting Baffle Filters - Intended for high airflow cooking. Their "S" shape design and Stainless Steel finish is crafted to capture significant amounts of grease.



Thermal barrier - The system detects extreme temperatures above 158 degrees and automatically increases the blower speed to HIGH.



Air Flow Control - AFC technology enables the user to reduce the maximum blower CFM achieving <300 CFMs,to meet local code requirements.



Fine precision - Constructed with great attention to detail with High-quality stainless steel, result in a seamless and flawless finish.



Superior performance - High performance ventilation with blowers ranging from 600 to 1200 CFM.

AIRFLOW CONTROL

Air Flow Control technology enables the user to reduce the maximum blower CFM of your hood achieving <300 CFMs,to meet local code requirements.

This model includes an Electronic Bypass Kit that needs to be placed at the moment of installing.

**ADA
COMPLIANT**

**AHAM
VERIFIDE**



* The product images shown are for illustration purposes only and may not be an exact representation of the product.

** CFM and Noise data indicate the performance of the hood blower tested according to international standards. For AHAM Certified Ratings, established in accordance with California Title 24 Standardized test procedure, please refer to AHAM Certified Product Directory. Electric Ratings are declared according to UL.