

SKSDR360S
36-INCH DUAL-FUEL PRO RANGE WITH
6 BURNERS



POWER-UP OR SIMMER DOWN

Two Ultra-High Burners deliver 23K BTUs of pure cooking power for better searing and quick stir frying. Two Ultra-Low Burners simmer down to maintain temperatures as low as 100° to prepare delicate sauces and sugary confections.

STEAM-COMBI CONVECTION OVEN

Spacious 6.3 cu. ft. capacity oven combines steam and convection cooking for gourmet results. The convection system cooks food quickly and evenly while steam helps to preserve texture, appearance and taste.

SPEEDCLEAN®

Makes fast work of cleaning a lightly-soiled oven with just a ten minute cycle, using only water.

BUILT-IN WOK GRATE

The three front burner grates are convertible for round-bottom wok cooking. Stir fry at home with professional-style results.

SMART KNOBS®

Each burner has a dedicated Smart Knob® featuring a large, illuminated display that makes it easy to read from across the room. Smart Knobs® include a Wi-Fi function that let you see if the burner is on or off using the ThinQ® app.

Innovation

Wi-Fi Enabled for ThinQ® Control with iPhone / Android App	Yes
Remote Operations	Yes
Remote Monitoring	Yes

Cooktop Features

Number of Burners	6
Continuous Grates	3
Wok Convertible Grate (On Front Burners)	Yes
Heating Element "ON" Indicator Light	Yes
LED Power Level Display	Yes

Cooktop Performance

Simmer – Max. BTU/h (NG)	
Left Rear	310 – 15,000
Center Rear	1,300 – 15,000
Right Rear	310 – 10,000
Left Front	650 – 23,000
Center Front	1,300 – 15,000
Right Front	650 – 23,000



SKSDR360S

36-INCH DUAL-FUEL PRO RANGE WITH 6 BURNERS

SKS | SIGNATURE
KITCHEN
SUITE

Oven Features & Performance

Oven Type	Steam-Combi Convection Oven
Oven Capacity (cu. ft.)	6.3
Special Cooking Modes	
ProHeat® Bake, ProHeat® Convection Bake, ProHeat® Convection Roast, Broil, Rapid Heat Roast+, Gourmet Chef, Steam-Combi, Gourmet Steam, Warm, Proof, My Recipe	
Convection System	ProHeat®
Convection Element	2,500 W
Convection Conversion	Yes
Broil Element	4,200 W
Bake Element	2,500 W
Steam Element	720 W
Oven Racks	2 Gliding & 1 Heavy Duty
Oven Meat Probe	Yes
Self Cleaning	Yes
Variable Time Self Cleaning (2-3-4 hrs.)	Yes
Speed Cleaning	Yes
Automatic Shut-Off (After 12 hrs.)	Yes
Star-K Certified Sabbath Mode	Yes
Interior Oven Light (Auto & Manual)	Yes

Controls

Touch Oven Controls with LCD Display	Yes
Knob Cooktop Controls w/LED Display	Yes
Electronic Clock & Timer	Yes
Control Lock (Oven Functions Only)	Yes
Delay Start Time	Yes
Mood Light	Yes
Preheat Alarm Light	On / Off
Audible Preheat Signal	Yes
Cooking Complete Reminder	Yes
Temperature Display (F or C)	Yes
Language Options	English, Spanish, French

Cooktop / General Features

Sealed Gas Burners (Brass)	Yes
Surface Material	Black Porcelain
Stainless Steel Side Panels	Yes
Door Lock	Yes

Technical Specs

Energy Source	Natural Gas and Electric
Alternative Energy Source	LP Gas and Electric
LP Conversion Kit Included	Yes
kW Rating at 240V	13.6 kW
Required Power Supply	240 / 208V, 60 Hz, 50 Amp

Dimensions and Weight

Overall Width (inches)	35 7/8
Overall Height Including Grates (inches)	36 11/16 to 38 1/8
Overall Depth Including Door (inches)	26 3/4
Overall Depth Including Handle (inches)	29 5/16
Net Weight (approx.)	375 lbs.
Shipping Weight (approx.)	495 lbs.

Accessories

Included Accessories
3 Wok Grates, 2 Gliding Racks, Heavy Duty Rack, Steam Tray, Broiler Pan, Grid, Meat Probe

Warranty Summary*

Limited Warranty, Parts & Labor	3 Years
---------------------------------	---------

*These warranties give you specific legal rights and you may have other rights that vary from state to state. For complete warranty details, refer to your Use & Care manual.

SKS | SIGNATURE
KITCHEN
SUITE

Diagram illustrating the minimum clearances for a range hood installation:

- Overhead Cabinets:** 36" (914 mm) min. distance between overhead cabinets or combustible material†.
- Range Hood Clearance:** 36" (914 mm) min. from bottom of hood to cooking surface.
- Combustible Sidewall:** 10" (254 mm) min. to combustible sidewall material (both sides)†.
- Range Width:** 36" (914 mm).
- Gas & Electrical Zone:** 7 5/8" (193 mm) height, 21" (533 mm) width, and 3 5/16" (84 mm) depth.
- Clearance to Combustible Material (Top):** 18" (457 mm) min.
- Clearance to Combustible Material (Bottom):** 36" (914 mm).
- Clearance to Combustible Material (Side):** 13" (330 mm) max. cabinet depth.
- Clearance to Combustible Material (Front):** 7 1/2" (190 mm) on each side of the range.

Electrical and Gas Specifications

Natural Gas or LP


Dual-Fuel Ranges are shipped by the factory to operate on natural gas. If the location / job site requires conversion from natural gas to propane (LP), utilize the included LP kit. Conversion must be done by a qualified installer or service technician.


SKSDR360S

36-INCH DUAL-FUEL PRO RANGE WITH 6 BURNERS

SKS | SIGNATURE
KITCHEN
SUITE

OVERALL PRODUCT DIMENSIONS





Page 1 of 4 | Effective 2/25

SKSIR360IS

36-INCH INDUCTION PRO RANGE



Oven Features & Performance

Oven Type	
Steam-Combi Convection Oven	
Oven Capacity (cu. ft.)	6.3
Special Cooking & Steam Modes	
ProHeat® Bake, ProHeat® Convection Bake, ProHeat® Convection Roast, Broil, RapidHeat Roast+, Auto Cook, Steam-Combi, Gourmet Steam, Warm, Proof, My Recipe, Air Fry, Steam Sous Vide	
Convection System	ProHeat®
Convection Element	2,500 W
Convection Conversion	Yes
Broil Element	4,200 W
Bake Element	2,500 W
Steam Element	720 W
Oven Racks	2 Gliding, 1 Heavy Duty
Oven Meat Probe	Yes
Self Cleaning	Yes
Variable Time Self Cleaning (3-4-5 hrs.)	Yes
Speed Cleaning	Yes
Automatic Shut-Off (After 12 hrs.)	Yes
Star-K Certified Sabbath Mode	Yes
Interior Oven Light (Auto & Manual)	Yes

Oven Controls

Touch Oven Controls with LCD Display	Yes
Display	7" TFT LCD
Electronic Clock & Timer	Yes
Control Lock (Oven Functions Only)	Yes
Delay Start Time	Yes
Mood Light	Yes
Preheat Alarm Light	On / Off
Audible Preheat Signal	Yes
Cooking Complete Reminder	Yes (Hi, Lo, Off)
Temperature Display (F or C)	Yes
Language Options	English, Spanish, French

General Features

Stainless Steel Side Panels	Yes
Door Lock	Yes

Technical Specs

Energy Source	Electric
Required Power Supply	240 / 208V, 60 Hz, 50 Amp

Dimensions and Weight

Overall Width (inches)	35 7/8
Overall Height (inches)	36 11/16 to 38 1/8
Overall Depth Including Door (inches)	26 3/4
Overall Depth Including Handle (inches)	29 5/16
Net Weight (approx.)	394.2 lbs.
Shipping Weight (approx.)	546.8 lbs.

Accessories

Included Accessories
2 Gliding Racks, Heavy Duty Rack, Steam Tray, Broiler Pan, Grid, Meat Probe, Air-Fry Rack

Warranty Summary*

Limited Warranty, Parts & Labor	3 Years
---------------------------------	---------

*These warranties give you specific legal rights and you may have other rights that vary from state to state. For complete warranty details, refer to your Use & Care manual.

PRELIMINARY PRELIMINARY PRELIMINARY PRELIMINARY PRELIMINARY



PRELIMINARY PRELIMINARY PRELIMINARY PRELIMINARY PRELIMINARY

PRELIMINARY PRELIMINARY PRELIMINARY PRELIMINARY PRELIMINARY

SKSIR360IS
36-INCH INDUCTION PRO RANGE

OVERALL PRODUCT DIMENSIONS

