

## Dynaudio Custom Install



OW-8 2-way on-wall

### On-wall outdoor loudspeaker series: authentic Dynaudio speakers, engineered to entertain

Quality doesn't need to stop at the door. Dynaudio Custom Outdoor speakers take our trademark audio quality to new places

Relaxing outside is always better with music. These two-way wall-mounted speakers are IP65-rated for total resistance to dust and protection from everyday water (such as sprinklers, rain and water-balloon fights). They have a UV-resistant finish and they've been subjected to salt-spray testing too – so they'll stand up to regular use whatever the weather throws at them.

The Outdoor range can be used in passive 8ohm mode, or linked in with a 70/100V system with their built-in transformers, if you want to spread them out to a larger area.

**Dynaudio heritage. Dynaudio craftsmanship... Dynaudio Custom.**

#### On-wall outdoor

- 2-way systems
- 6in and 8in versions
- IP65 rated
- 8 Ω / 70 V / 100 V
- Articulated wall bracket
- Black and white UV-resistant finishes

### OW-8

#### SPECIFICATIONS

<b>Dynaudio Custom Architectural Studio range</b>		On-wall 8in
<b>Description</b>		2-way on-wall
<b>Drivers</b>	Tweeter	28mm / 1in
	Woofer	200mm / 8in
<b>Performance</b>	Frequency response (+/- 3dB)	70Hz – 20kHz
	Impedance (nominal/minimum)	8Ω / 5Ω
	Continuous power	60W
	Long-term power	300W
	Sensitivity (dB SPL (2.83V/1m))	87
	Maximum input voltage	100Vrms
	Input selector	8Ω / 70V / 100V
<b>Dimensions</b>	W x H xD	210 x 340 x 196 mm
		(8 <sup>1</sup> / <sub>4</sub> x 13 <sup>3</sup> / <sub>8</sub> x 7 <sup>9</sup> / <sub>16</sub> in)
<b>Weight</b>		5kg
<b>Temperature range</b>		-33°C to +40°C (-27.4°F to 111.2°F)