

10. DALI EPIKORE Specifications

	EPIKORE 3	EPIKORE 7	EPIKORE 9	EPIKORE 11
Frequency range	42 - 34,000 Hz ±3 dB	35 - 34,000 Hz ±3 dB	29 - 34,000 Hz ±3 dB	29 - 34,000 Hz ±3 dB
Sensitivity	85 dB @ 1 m for 2.83 V	88 dB @ 1 m for 2.83 V	88 dB @ 1 m for 2.83 V	89 dB @ 1 m for 2.83 V
Nominal impedance	6 Ohm	6 Ohm	4 Ohm	4 Ohm
Maximum SPL	108 dB	110 dB	112 dB	116 dB
Crossover frequency	2,800 / 12,500 Hz	800 / 2,500 / 12,500 Hz	400 / 3,100 / 12,500 Hz	170 / 370 / 3,100 / 12,500 Hz
Crossover principle	3-way	3½-way	4-way	4½-way
Recommended amplifier power	40 - 250 Watt	40 - 400 Watt	40 - 500 Watt	40 - 1,000 Watt
High frequency driver(s)	10 × 55 mm planar magnetostatic tweeter 1 × 35 mm soft dome	10 × 55 mm planar magnetostatic tweeter 1 × 35 mm soft dome	10 × 55 mm planar magnetostatic tweeter 1 × 35 mm soft dome	10 × 55 mm planar magnetostatic tweeter 1 × 35 mm soft dome
High frequency diaphragm	Planar magnetostatic Soft woven fabric	Planar magnetostatic Soft woven fabric	Planar magnetostatic Soft woven fabric	Planar magnetostatic Soft woven fabric
Low/Mid frequency driver(s)	1 × 7 inch	2 × 7 inch	2 × 8 inch 1 × 6½ inch	4 × 8 inch 1 × 6½ inch
Low/Mid frequency diaphragm	Clarity Cone™ paper and wood fibre	Clarity Cone™ paper and wood fibre	Clarity Cone™ paper and wood fibre	Clarity Cone™ paper and wood fibre
Connection input(s)	Bi-wire	Bi-wire	Bi-wire	Bi-wire
Enclosure type	Bass reflex	Bass reflex	Bass reflex	Bass reflex
Bass reflex tuning frequency	39 Hz	33 Hz	27 Hz	24 Hz
Other features	N/A	N/A	N/A	N/A
Recommended placement	Stand or shelf	Floor	Floor	Floor
Recommended distance from rear wall	35 - 120 cm	35 - 120 cm	35 - 120 cm	35 - 120 cm
Dimensions (H × W × D)	470 × 250 × 420 mm 18.5 × 9.8 × 16.5 inches	1120 × 380 × 420 mm 44.1 × 15.0 × 16.5 inches	1310 × 422 × 554 mm 51.6 × 16.6 × 21.8 inches	1602 × 422 × 554 mm 63 × 16.6 × 21.8 inches
Weight incl. grille	22.0 kg 48.5 lb	40.5 kg 89.3 lb	64.0 kg 141.1 lb	72 kg 158.7 lb
Shipping weight	51.2 kg (pair) 112.9 lb (pair)	97.6 kg (pair) 215.2 lb (pair)	143.0 kg (pair) 315.3 lb (pair)	177 kg (pair) 390.2 lb (pair)
Finishes	High Gloss Black (Shadow Black grille) High Gloss Walnut (Shadow Black grille) High Gloss Maroon (Shadow Black grille)	High Gloss Black (Shadow Black grille) High Gloss Walnut (Shadow Black grille) High Gloss Maroon (Shadow Black grille)	High Gloss Black (Shadow Black grille) High Gloss Walnut (Shadow Black grille) High Gloss Maroon (Shadow Black grille)	High Gloss Black (Shadow Black grille) High Gloss Walnut (Shadow Black grille) High Gloss Maroon (Shadow Black grille)
Accessories (pair)	4 × Terminal jumpers 1 × Cleaning cloth 2 × Magnetic front grille 8 × Rubber Feet	8 × Magnetic spike feet 4 × Terminal jumpers 1 × Cleaning cloth 2 × Magnetic front grille 4 × Floor protection pads	8 × Magnetic spike feet 4 × Terminal jumpers 1 × Cleaning cloth 2 × Magnetic front grille 4 × Floor protection pads	8 × Magnetic spike feet 4 × Terminal jumpers 1 × Cleaning cloth 2 × Magnetic front grille 4 × Floor protection pads
Optional accessories:	EPIKORE STAND	N/A	N/A	N/A
Spike thread size:	M6	M12	M12	M12

All technical specifications are subject to change without notice.