

Monitor Section

Picture size	6.2 inches(diagonal) wide
W x H	5-7/16 x 3-1/16
Display system	Transparent TN LCD panel
Drive system	TFT active matrix system
Number of pixels	800H x 480V x RGB
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter	24Bit
Audio Decoder	Linear PCM
	Dolby Audio
	MP3/WMA/AAC(.m4a)/WAV
Video Decoder	MPEG1/MPEG2/JPEG
Wow & Flutter	Below Measurable Limit
Frequency response	20 - 22,000 Hz
Sampling	96k
Sampling	48k
Sampling	44.1k
Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.0001
Signal to Noise ratio	90dB
Dynamic range	90dB
DISC Format	DVD-Video/VIDEO-CD/CD-DA
Sampling frequency	44.1kHz/48kHz
	96kHz
Quantifying bit number	16/20/24bit

USB I/F Section

USB Standard	USB2.0 Full Speed / High Speed
Compatible Devices	Mass storage class
File System	FAT 16/32
Maximum Power Supply Current	DC5V (DC logo) = 1.5A
D/A Converter	24bit
Audio Decoder	MP3/WMA/AAC(.m4a/.aac)/WAV/FLAC
Video Decoder	MPEG1/MPEG2/JPEG

Monitor Section

Picture size	6.2 inches(diagonal) wide
W x H	5-7/16 x 3-1/16
Display system	Transparent TN LCD panel
Drive system	TFT active matrix system
Number of pixels	800H x 480V x RGB
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter	24Bit
Audio Decoder	Linear PCM
	Dolby Audio
	MP3/WMA/AAC(.m4a)/WAV
Video Decoder	MPEG1/MPEG2/JPEG
Wow & Flutter	Below Measurable Limit
Frequency response	96k
Sampling	20 - 22,000 Hz
	48k
Sampling	20 - 22,000 Hz
	44.1k
Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.0001
Signal to Noise ratio	90dB
Dynamic range	90dB
DISC Format	DVD-Video/VIDEO-CD/CD-DA
Sampling frequency	44.1kHz/48kHz
	96kHz
Quantifying bit number	16/20/24bit

USB I/F Section

USB Standard	USB2.0 Full Speed / High Speed
Compatible Devices	Mass storage class
File System	FAT 16/32
Maximum Power Supply Current	DC5V (DC logo) = 1.5A
D/A Converter	24bit
Audio Decoder	MP3/WMA/AAC(.m4a/.aac)/WAV/FLAC
Video Decoder	MPEG1/MPEG2/JPEG

Monitor Section

Picture size	6.2 inches(diagonal) wide
W x H	5-7/16 x 3-1/16
Display system	Transparent TN LCD panel
Drive system	TFT active matrix system
Number of pixels	800H x 480V x RGB
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter	24Bit
Audio Decoder	Linear PCM
	Dolby Audio
	MP3/WMA/AAC(.m4a)/WAV
Video Decoder	MPEG1/MPEG2/JPEG
Wow & Flutter	Below Measurable Limit
Frequency response	96k
Sampling	20 - 22,000 Hz
	48k
Sampling	20 - 22,000 Hz
	44.1k
Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.0001
Signal to Noise ratio	90dB
Dynamic range	90dB
DISC Format	DVD-Video/VIDEO-CD/CD-DA
Sampling frequency	44.1kHz/48kHz
	96kHz
Quantifying bit number	16/20/24bit

USB I/F Section

USB Standard	USB2.0 Full Speed / High Speed
Compatible Devices	Mass storage class
File System	FAT 16/32
Maximum Power Supply Current	DC5V (DC logo) = 1.5A
D/A Converter	24bit
Audio Decoder	MP3/WMA/AAC(.m4a/.aac)/WAV/FLAC
Video Decoder	MPEG1/MPEG2/JPEG

Monitor Section

Picture size	6.2 inches(diagonal) wide
W x H	5-7/16 x 3-1/16
Display system	Transparent TN LCD panel
Drive system	TFT active matrix system
Number of pixels	800H x 480V x RGB
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter	24Bit
Audio Decoder	Linear PCM
	Dolby Audio
	MP3/WMA/AAC(.m4a)/WAV
Video Decoder	MPEG1/MPEG2/JPEG
Wow & Flutter	Below Measurable Limit
Frequency response	96k
Sampling	20 - 22,000 Hz
	48k
Sampling	20 - 22,000 Hz
	44.1k
Sampling	20 - 20,000 Hz
Total harmonic distortion 1kHz	0.0001
Signal to Noise ratio	90dB
Dynamic range	90dB
DISC Format	DVD-Video/VIDEO-CD/CD-DA
Sampling frequency	44.1kHz/48kHz
	96kHz
Quantifying bit number	16/20/24bit

USB I/F Section

USB Standard	USB2.0 Full Speed / High Speed
Compatible Devices	Mass storage class
File System	FAT 16/32
Maximum Power Supply Current	DC5V (DC logo) = 1.5A
D/A Converter	24bit
Audio Decoder	MP3/WMA/AAC(.m4a/.aac)/WAV/FLAC
Video Decoder	MPEG1/MPEG2/JPEG

Monitor Section

Picture size	6.2 inches(diagonal) wide
W x H	5-7/16 x 3-1/16
Display system	Transparent TN LCD panel
Drive system	TFT active matrix system
Number of pixels	800H x 480V x RGB
Pixel arrangement	RGB striped arrangement
Back lighting	LED

DVD Section

D/A Converter	24Bit
Audio Decoder	Linear PCM
	Dolby Audio
	MP3/WMA/AAC(.m4a)/WAV
Video Decoder	MPEG1/MPEG2/JPEG
Wow & Flutter	Below Measurable Limit
Frequency response Sampling	96k 20 - 22,000 Hz
Sampling	48k 20 - 22,000 Hz
Sampling	44.1k 20 - 20,000 Hz
Total harmonic distortion 1kHz	0.0001
Signal to Noise ratio	90dB
Dynamic range	90dB
DISC Format	DVD-Video/VIDEO-CD/CD-DA
Sampling frequency	44.1kHz/48kHz
	96kHz
Quantifying bit number	16/20/24bit

USB I/F Section

USB Standard	USB2.0 Full Speed / High Speed
Compatible Devices	Mass storage class
File System	FAT 16/32
Maximum Power Supply Current	DC5V (DC logo) = 1.5A
D/A Converter	24bit
Audio Decoder	MP3/WMA/AAC(.m4a/.aac)/WAV/FLAC
Video Decoder	MPEG1/MPEG2/JPEG