

ARG12PV



61.75" x 23.38" x 24.38" (H x W x D)

Performance series Pharma-Vac 12 cu.ft. upright glass door commercial all-refrigerator for the display and refrigeration of vaccines

Highlights:

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Additional sensor reads interior air temperature for superior temperature control

Product Features:

| | |
|---|--|
| Purpose-built design | Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC guidelines |
| +/-1°C Variation | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period |
| Commercial design | Meets UL-471 commercial standards |
| Adjustable temperature | Intuitive controls let you adjust the interior temperature between +2 to +8°C |
| Temperature alarm | Visual and audible alarms alert if the interior temperature rises or falls out of set range |
| Remote alarm contacts | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) |
| Automatic defrost with adjustable cycle defrost | Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup |
| Access port | Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment |
| Open door alarm | Alarm will sound if the door is left ajar for over 4 minutes (adjustable from 1-99 minutes) |

ARG12PV Specifications:

Overview

| | |
|----------------------------|---------------------|
| Height of Cabinet | 61.75" (157 cm) |
| Width | 23.38" (59 cm) |
| Width with Door Open | 23.88" (61 cm) |
| Depth | 24.38" (62 cm) |
| Depth with Handle | 26.13" (66 cm) |
| Depth with door at 90° | 46.5" (118 cm) |
| Capacity | 12.0 cu.ft. (340 L) |
| Defrost Type | Automatic |
| Door | Glass |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 1.4 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 188.7 lbs. (86 kg) |
| Shipping Weight | 207.2 lbs. (94 kg) |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |

Refrigerator Features

| | |
|--------------------|----------|
| Door Swing | RHD |
| Reversible | Yes |
| Shelf Type | Wire |
| Shelf Qty | 7 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R600a |
| Refrigerant Amount | 2.11oz. |
| Interior Light | Yes |
| Temperature Range | 2 to 8°C |

Dimensions

| | |
|------------------------|----------------|
| Interior Height | 53.0" (135 cm) |
| Interior Width | 20.0" (51 cm) |
| Interior Depth | 17.0" (43 cm) |
| Compressor Step Height | 6.5" (17 cm) |
| Compressor Step Width | 20.0" (51 cm) |
| Compressor Step Depth | 5.0" (13 cm) |

