

PowerLite® L890U

8,000-Lumen WUXGA 3LCD
Laser Projector



**Experience an ultra bright
and compact projector
with pro-level features.**



Ultra bright, true-to-life images — 3-chip 3LCD technology and 8,000 lumens of equal color and white brightness¹

Full HD WUXGA resolution — accepts up to 4K signal and provides 1920 x 1200 resolution for vibrant, high-definition images

Large, versatile display options — easily create a display up to 500" diagonal in 16:10, plus ultra wide 16:6 and 21:9 aspect ratios for enhanced content display and visibility

Simplified installation — compact and lightweight design featuring wide vertical and horizontal lens shift, 1.6x optical zoom, 360-degree mounting, built-in geometric correction tools and a universal VESA mounting pattern

Low maintenance — up to 30,000-hour laser light source and air filter² in Extended Mode

Wireless networking and content sharing³ — Wi-Fi® 6/6E allows for fast, reliable wireless connectivity for screen casting³, along with direct connection to the cloud-based service, Epson Projector Management Connected and WPA3-Enterprise security

Works with Apple® AirPlay® 2 — wirelessly stream videos, music, photos and presentations to your projector right from your iPhone®, iPad® or Mac^{®4}

Built-in NFC⁵ — reduces installation time of multiple projectors; read and write setting information using the Epson Projector Config Tool app

Optional attachable PixAlign™ camera — adds powerful multi-projector tools including screen matching⁶, auto color calibration⁶, blending assist⁷ for super wide displays and simple stacking⁷ without an external PC

Over-the-air updates⁸ — allows user to optionally be alerted when a Firmware update is available

Enhanced connectivity — HDBaseT® and HDMI® two in and one out for daisy-chaining and signal monitoring

Specifications

Projection System RGB liquid crystal shutter projection system

Projection Method Front/rear/ceiling mount

LCD Size 0.67" (C-Fine)

Driving Method Poly-Silicon TFT Active Matrix

Pixel Number 2,304,000 dots (1920 x 1200) x 3

Native Resolution 1920 x 1200 (WUXGA)

Resolution On-Screen 1920 x 1200 (WUXGA)

Resize 640 x 480, 800 x 600, 1280 x 1024, 1400 x 1050

Aspect Ratio Supports 4:3, 16:10, 16:9*, 16:6*, 21:9*

* With vertical image shift control within letterbox area.

Pixel Arrangement Cross stripe

Color Brightness¹ Color light output: 8,000 lumens

White Brightness¹ White light output: 8,000 lumens

Contrast Ratio Over 5,000,000:1

Brightness Uniformity (Typical) 88%

Color Reproduction Up to 1.07 billion colors

Size (Projected Distance) 50" – 500"

Projected Distance 80" screen 2.33 m – 3.78 m

Lens Shift (Manual) Vertical: ±50%; Horizontal: ±20%

Keystone Correction Vertical: ±30 degrees;

Horizontal: ±30 degrees

Light Source Laser Diode

Laser Light Source Life² Normal: 20,000 hours; Quiet: 20,000 hours; Extended: 30,000 hours

Projection Lens (Standard)

Type Optical Zoom (manual)/Focus (manual)

F-Number 1.5 – 1.7

Focal Length 20.0 mm – 31.8 mm

Zoom Ratio 1.0 – 1.6x (optical)

Throw Rate Range 1.35 – 2.20 (optical)

Lens Cover Lens cap (without string)

Wireless Specifications

Frequency Type (Modulations) 802.11 b/g/n/ac/ax (2.4 GHz)

Supported Security Type Quick Mode: Open, WPA/WPA3-PSK, WPA2/WPA3-EAP; Advanced Mode: WPA/WPA2-PSK, WPA/WPA2-EAP

Other Features

Operating Temperature 32 °F to 113 °F (0 °C to 45 °C)

Power Supply Voltage 100 V – 240 V ± 10%, 50/60 Hz AC

Auto Power On Signal Detection on HDMI/Plug-In Detection

Sleep Mode Yes (with timer)

HDMI CEC Control Yes

Power Consumption

470 W (Normal Mode)

341 W (Quiet and extended)

2.4 W (Standby comm on)

0.3 W (Standby comm off)

Fan Noise 31 dB (Normal Mode); max. 23 dB (ECO Mode)

Security Security cable hole, Kensington® lock provision

Miracast³ Yes

Epson iProjection^{™3} Yes (V4)

Apple Airplay 2⁴ Yes

Split Screen⁵ Yes (up to 2 screens)

1 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. 2 No required maintenance for the light source and filter for up to 30,000 hours (Extended Mode) or 20,000 hours (Normal Mode). Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. 3 The projector supports direct peer-to-peer wireless casting of local content from Miracast-enabled devices or via the Epson iProjection app. For best performance when using Epson iProjection, it is recommended that the projector and connecting devices be configured on a network, either through the Ethernet port on the projector or via a wireless connection. The Epson iProjection App does not support all files and formats. See epson.com/iprojection for details. 4 AirPlay requires an active Internet connection and Firmware version V200 or higher. To download the latest Firmware, please visit the support page for your specific product on www.epson.com. 5 NFC requires use of a device that includes NFC and may require additional software. 6 Using separate camera for each projector. 7 Requires Epson external camera for each projector and may require Epson Projector Professional Tool app. 8 Requires an active Internet connection for alerts and Firmware download. 9 Split Screen feature requires remote control. Consult your user manual for input combinations. 10 For convenient and reasonable recycling options, visit epson.com/recycle. 11 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. 12 Product comes with a 3-year limited warranty with the option to purchase Extended Service Plans up to a total of 5 years of continuous coverage. Extended Service Plan can be purchased at any time that you are covered under an Epson limited warranty or Epson Extended Service Plan. See individual service plan for details. 13 Expedited shipping not available in all areas. Orders must be placed and processed by 1 p.m. Pacific Time, Monday through Friday, excluding holidays.

See the latest innovations from Epson Business Solutions at epson.com/forbusiness



Epson America, Inc.
3131 Katella Ave., Los Alamitos, CA 90720

Epson Canada Limited
185 Renfrew Drive, Markham, Ontario L3R 6G3

epson.com
epson.ca

Specifications and terms are subject to change without notice. EPSON, the 3LCD logo and PowerLite are registered trademarks and Epson iProjection is a trademark of Seiko Epson Corporation. Epson Connection, Epson Preferred Plus, Pilot and PixAlign are trademarks of Epson America, Inc. AirPlay, Apple, iPad, iPhone and Mac are trademarks of Apple Inc., registered in the U.S. and other countries. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. Miracast® and Wi-Fi® are registered trademarks of Wi-Fi Alliance®. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2025 Epson America, Inc. CPD-65471R1/25

Interfaces

HDMI (HDCP 2.3) x 2

HDMI Out x 1

HDBaseT x 1

Variable Audio Out: Mini Stereo x 1

USB Connector Type-A x 1

USB Connector Type-B x 1

Serial: RS-232c x 1

Wired LAN RJ45 x 1

Wireless LAN: Built-in



Other Features (Continued)

A/V Mute Yes

Camera Optional

Speaker(s) 10 W (mono)

Content Playback Yes

Quick Corner Yes

Corner Wall Yes

Curved Surface Yes

Edge Blending Yes

Screen Sharing Yes

Effective Scanning Frequency Range (Digital)

Pixel Clock 25.1 MHz – 594 MHz

Horizontal 26 kHz – 135 kHz

Vertical 23.98/24/25/29.97/30/50/59.94/60 Hz

Dimensions (W x D x H)

Excluding Feet 17.32" x 11.97" x 4.80"

Including Feet 17.32" x 13.39" x 5.43"

Weight 19.1 lb

Network and Remote Control

Features Power, source search selection, A/V Mute, number input, menu, esc, select, Freeze, ID, Customize, E-Zoom, mute, volume, playback control and pointer functions

Operating Angle Rear: Right/Left: -55 to +55 degrees; Upper/Lower: +75 to +15 degrees; Front: Right/Left: -30 to +30 degrees; Upper/Lower: 0 to +60 degrees

Operating Distance 26 ft (8 m)

Network Control PJLink, Crestron® Integrated partner, Crestron Connected V2 with XIO Cloud, Extron® IP link, Extron XTP, AMX®, Control4®

Eco Features

RoHS compliant

End-of-life options available¹⁰

Epson America, Inc. is a SmartWay® Transport Partner¹¹

Design and Manufacturing centers utilize 100% renewable electricity

Dynamic Contrast (ECO) Mode reduces power consumption by 36%

Limited Warranty and Service

Warranty Three-year limited in the U.S. and Canada

Service Whole unit exchange, usually Next-Business-Day

Toll-free telephone support, Monday through Friday

Epson Connection™

Pre-Sales Support (U.S. and Canada): 800-463-7766

Website: www.epson.com

Epson Preferred Plus™ Extended Service Plan

1-Year Next-Business-Day Whole Unit Exchange^{12,13} EPPEPE1

2-Year Next-Business-Day Whole Unit Exchange^{12,13} EPPEPE2

(available for up to a total of 5 years of continuous coverage)

What's Included

PowerLite L890U laser projector, power cable, projector remote control with batteries, Quick Reference card, cable cover

Ordering Information & Accessories

PowerLite L890U V11HB27020

Replacement Air Filter (ELPAF65) V13H134A0

Custom Micro-Adjustable Projector Mount (ELPMBPRH) V12H809001

Universal Projector Mount (ELPMBPJG) V12H808001

PowerLite Pilot™ 3R (ELPCB03N) V12HB11020

PixiePlus ELPSP10

PixAlign Camera (ELPEC01) V12HA46010

External Speaker (ELPSPO2) V12H467020

DC-07 Document Camera V12H759020

DC-13 Document Camera V12H757020

DC-21 Document Camera V12H758020

Contact: