

Product data sheet

CONSTRUCTION TYPE AND DESIGN

Combi-Steam Oven	•
PureLine	•
PureLine	•
Combi-Steam Oven	•
Appliance colour	CleanTouch Steel

CONVENIENCE FEATURES

Miele Mix & Match	•
Rapid PreHeat	•
Rapid PreHeat	•
Preheating	•
Preheating	•
External steam generation	•
External steam generation	•
Oxygen sensor	•
Oxygen sensor	•
Individual humidity settings in combination cooking	•
Individual humidity settings in combination cooking	•
Menu cooking without transfer of flavours	•
Menu cooking without transfer of flavours	•
Food probe	With cable

MasterChef programs with ability to make individual adjustments	•
--	---

MasterChef programs with ability to make individual adjustments	•
--	---

Keeping warm	•
---------------------	---

Keeping warm	•
---------------------	---

Crisp function	•
-----------------------	---

Crisp function	•
-----------------------	---

OPERATING MODES

Convection Bake	•
------------------------	---

Convection Roast	•
-------------------------	---

•

Combination cooking	•
----------------------------	---

Combination cooking with Convection Bake	•
---	---

Combination cooking with Surround	•
--	---

Combination cooking with Maxi Broil	•
--	---

Steam cooking	•
----------------------	---

Sous-vide	•
------------------	---

Maxi Broil	•
-------------------	---

Intensive	•
------------------	---

Humidity Plus	•
----------------------	---

Surround	•
-----------------	---

Browning	•
-----------------	---

Bake	•
-------------	---

Convection Broil	•
-------------------------	---

Special modes	•
----------------------	---

Defrost	•
----------------	---

MasterChef programs	•
----------------------------	---

MasterChef programs	•
Country-specific MasterChef programs	•
Country-specific MasterChef programs	•
Combination cooking with Convection Bake	•
Combination cooking	•
Combination cooking with Surround	•
Combination cooking with Maxi Broil	•
Steam cooking	•
Sous-vide	•
Reheat	•
Reheat	•
Roast with moisture	•
Roast with moisture	•
Maxi Broil	•
Broil	•
Broil	•
Intensive	•
Humidity Plus	•
Surround	•
Browning	•
Bake	•
Convection Broil	•
Plate warming	•
Plate warming	•
Special modes	•
Broiling operating modes	•
Broiling operating modes	•

USER CONVENIENCE

Clear text on control panel	•
Display	M Touch S
SoftOpen	•
SoftOpen	•
SoftClose	•
SoftClose	•
Language Options	•
Language Options	•
MyMiele	•
MyMiele	•
Help function	•
Help function	•
Motorized lift-up control panel	•
Motorized lift-up control panel	•
Quantity-independent cooking	•
Quantity-independent cooking	•
Steam cook simultaneously on up to 3 levels	•
Steam cook simultaneously on up to 3 levels	•
Automatic menu cooking	•
Automatic menu cooking	•
Steam reduction before end of program	•
Steam reduction before end of program	•
Time-of-day display	•
Time-of-day display	•
Date display	•
Date display	•

Timer	•
Timer	•
Programmable start of cooking duration	•
Programmable start of cooking duration	•
Programmable end of cooking duration	•
Programmable end of cooking duration	•
Programmable cooking duration	•
Programmable cooking duration	•
Actual temperature display	•
Actual temperature display	•
Desired temperature display	•
Desired temperature display	•
Audible signal when desired temperature is reached	•
Audible signal when desired temperature is reached	•
Recommended temperatures	•
Recommended temperatures	•
Favourites	•
Favourites	•
Sabbath Program	•
Sabbath Program	•
Individual settings	•
Individual settings	•
Networking with Miele@home	•
Networking with Miele@home	•
Display	M Touch S
Timers	•
Timers	•

MotionReact DG	•
MotionReact DG	•

CLEANING CONVENIENCE

Maintenance programs	•
Maintenance programs	•
Stainless steel / Clean Touch Steel surface	•
Stainless steel oven compartment with linen-weave pattern and PerfectClean finish	•
External steam generator	•
Automatic descaling	•
CleanGlass door	•
Stainless steel / Clean Touch Steel surface	•
Stainless steel oven compartment with linen-weave pattern and PerfectClean finish	•
Hinged broiler	•
Hinged broiler	•
External steam generator	•
Separate soak	•
Separate soak	•
Rinse program	•
Rinse program	•
Oven compartment drying program	•
Oven compartment drying program	•
Quick-release side racks	•
Quick-release side racks	•
Removable side racks	•
Removable side racks	•
Descaling	•

CleanGlass door

•

STEAM TECHNOLOGY AND WATER SUPPLY**MultiSteam**

•

MultiSteam

•

Condensate container behind motorized lift-up control panel

•

Condensate container behind motorized lift-up control panel

•

Drain filter

•

Drain filter

•

Fresh-water container tank behind motorized lift-up control panel

•

Fresh-water container volume in l

1.4

Fresh-water container volume in l

1.4

SAFETY**Appliance cooling system with touch-cool fronts**

•

Safety shut-off

•

System lock

•

Appliance cooling system with touch-cool fronts

•

Safety shut-off

•

System lock

•

Steam cooling system

•

Steam cooling system

•

Sensor lock

•

Sensor lock

•

TECHNICAL DATA

Replacing lamps	Customer Service
Oven mode temperatures in °F (°C)	85-450 °F (30-230 °C)
Oven interior lighting	BrilliantLight
Number of shelf levels	3
Numbered shelf levels	•
Numbered shelf levels	•
Oven interior lighting	BrilliantLight
Niche width min. in inches (mm)	22 1/8 (560)
Niche width min. in inches (mm)	560
Niche width max. in inches (mm)	22 3/8 (568)
Niche width max. in inches (mm)	568
Niche height min. in inches (mm)	450
Niche height min. in inches (mm)	17 3/4 (450)
Niche height max. in inches (mm)	17 7/8 (452)
Niche height max. in inches (mm)	452
Niche depth in mm	21 7/8 (555)
Niche depth in mm	555
Appliance width in mm	595
Appliance width in mm	23 1/2 (595)
Appliance height in mm	18 (456)
Appliance height in mm	455.5
Appliance depth in mm	22 1/2 (569)
Appliance depth in mm	568.5
Weight in lbs (kg)	91 (41.2)
Weight in lbs (kg)	91 (41.2)
Weight in lbs (kg)	90.83 (41.2)

Total rated load in kW	2.800-3.700
Total rated load in kW	2.800-3.700
Voltage in V	0
Voltage in V	0
Usable voltage range in V	240/208
Usable voltage range in V	240/208
Frequency in Hz	60
Frequency in Hz	60
Fuse rating in A	20
Fuse rating in A	20
Number of phases	2
Number of phases	2
Power cable with plug	•
Length of power cable in m	2
Length of power cable in m	2
Appliance dimensions (W x H x D) in mm	23 1/2 (595) x 18 (456) x 22 1/2 (569)
Appliance dimensions (W x H x D) in mm	23 1/2 (595) x 18 (456) x 22 1/2 (569)
Niche dimensions (W x H x D) in mm	560-568 x 450-452 x 555
Door hinging	Bottom

ACCESSORIES SUPPLIED

FlexiClip Runners with PerfectClean (pair)	1
Universal tray with PerfectClean	1
Universal tray with PerfectClean	1
Wire rack with PerfectClean	1
Wire rack with PerfectClean	1
FlexiClip Runners with PerfectClean (pair)	1

Removable side racks with PerfectClean (pair) 1

Removable side racks with PerfectClean (pair) 1

Perforated stainless-steel cooking containers 1

Perforated stainless-steel cooking containers 1

Solid stainless-steel cooking containers 1

Solid stainless-steel cooking containers 1

Descaling tablets 2

Descaling tablets 2

AVAILABLE DISPLAY LANGUAGES

Available display languages via Language Options bahasa malaysia