BRGAN[®] Elite

Under-Cabinet

TENAYA

Tenaya is a slim, transitional design with gentle radius features which makes it perfect for todays contemporary kitchens. This beautiful design includes features that make it a pleasure to use and easy to maintain. The LED modules included with this hood are the latest in LED cooktop illumination technology specially designed to operate in the elevated temperatures of cooking - offering bright lighting and lasting up to 25 times as long as a standard bulb and greater reliability than typical replacement LED bulbs.

SIZE	ZE BLACK STAINL		ESS WHITE		GREASE FILTERS (replacement)				NON-DUCTED FILTERS		
30 in.	TEN230BL	TEN230S	S TEN230	WW H	HPFAMM30 (Type "C1" / "C2")			") ⊢	IPF30 (Type	"Xc")	
36 in.	TEN236BL	TEN236S	S TEN236		HPFAMM36 (Type "				HPF36 (Type "Xd")		
42 in.		TEN242S			HPFAMM42			,	IPF42 (Type		
	RFORMANCE			1		() I				,	
					Sones				CFM		
Duct Orientation		Size	Damper						High High		
				Normal	Medium*	High	Normal	Medium*	0.25 in. w.g.	0.1 in. w	
Vertical - Rectangular		3¼ in. x 10 in.	Included	1.2			110	160	160	240	
Horizontal - Rectangular		3¼ in. x 10 in.	Included	1.2	3.0	6.0	110	160	160	240	
Round - Vertical		7 in.	Sold Separately	1.5	3.0	5.5	120	180	140	260	
EATUR	ES										
Max. Blower Airflow		375 CFM									
Control type		3-speed Capacitive Touch									
Delay off		no									
Filter Clean Reminder		yes									
Heat Sentry™		no						(413)			
ADA Capable		yes									
Lighting		2-level LED (included)									
Grease Filters		Micro Mesh (Qty. 2)									
Installation Hardware		EZ1 Bracket									
ENERGY STAR®		no									
Recirculation		Non-ducted filters sold separately				-			Onint		
AC INPL	JT					1	1000	50			
120 V, 6	60 Hz - 0.65 A	AMPS						0.0			
OPTION	AL ACCESS	ORIES			-		C				
7-in. Round Damper		BP87Q					-				
ADA Wiring Kit		HAWRK3									
Make-up Air Dampers		MD6TU, MD8TU and MD10TU						۵			
	ING HEIGHT										
		ooktop to bottom	of hood								
	WARRANTY										
l-year											
3-year (l	ED modules	only)				50	<		→ <i>⋆</i>		
See ins	tallation manua	al for full warrant	y text.)		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~) Ex	//		àr _	
OR IN	DOOR USE C	DNLY			4	00,0		\nearrow	NO X	\mathbf{X}	
0.6				ed.		X	$ \land $	/ The second		52 5	
0.5			7-in. round	_			$\langle \bullet \rangle$			X	
0.4			Vertical High Spee with 3¼ in. x 10 ir			\searrow			51		
			Horizontal High S						5 1 7 418 358 Dime		
0.3			with 3¼ in. x 10 in				211	JA 1	358		
0.2							`'ê 🦯	298	Dime	nsions	
0.1								Y		n inches	
0											
	50 100	150 200	250 200								
0	50 100	150 200 Airflow (cfm)	250 300	350							



* Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure.

CERTIFIED

99046193C