

Specifications

Turntable

Motor	DC motor
Drive Method	Belt-drive
Speeds	33-1/3 RPM, 45 RPM
Turntable Platter	Die-cast aluminium
Wow and Flutter	< 0.25% (WTD)
Signal-to-Noise Ratio	> 55 dB
Cartridge Type	This product is equipped with an AT-VM95C Dual Moving Magnet Stereo Cartridge. The cartridge cannot be removed.
Output Level	PHONO: 4.0 mV nominal at 1 kHz, 5 cm/sec LINE: 252 mV nominal at 1 kHz, 5 cm/sec
Phono Pre-Amp Gain	36 dB nominal, RIAA equalized
Power Consumption	1.6 W
Dimensions	400 mm (16") × 330 mm (13") × 110 mm (4.3") (W × D × H)
Weight	Approx. 2.9 kg (6.4 lbs)
Accessories Included	<ul style="list-style-type: none">• Dust cover• Felt mat• Platter (with drive belt)• Dust cover hinges• 45 RPM adapter• RCA audio cable (Approx. 1.0 m (3.3'))• AC adapter (Approx. 1.5 m (4.9'))
AC Adapter	*Type: FJ-SW1261200500DN Rated Input Voltage: 100 to 240 V AC Rated Input Current: 0.4 A max. Rated Frequency: 50 Hz / 60 Hz Rated Output Voltage: 12 V DC Rated Secondary Current: 0.5 A Cable Length: Approx. 1.5m (4.9')
Effective Arm Length	220 mm (8.7")
Overhang	18 mm (0.71")
Tracking Error Angle	Less than 2.0°
Replacement Stylus	AT-VMN95C (sold separately)
Replacement Belt	AT-LP70X exclusive belt (sold separately)
Communication System	Bluetooth version 5.2
Frequency Band	2.402 GHz to 2.480 GHz
Maximum RF Output	2.5 mW EIRP
Maximum Communication Range	Line of sight - approx. 10 m (33')
Modulation Method	GFSK, Pi/4DQPSK, 8DPSK
Compatible Bluetooth Profile	A2DP
Support Codec	Qualcomm® aptX™ Adaptive audio, Qualcomm® aptX™ audio, SBC
Notes	*The included AC adapter may differ depending on the country of sale. Check the rating label on the AC adapter. For details, contact your local Audio-Technica dealer. For product improvement, the product is subject to modification without notice.