

# Product data sheet

## CONSTRUCTION TYPE AND VERSION

Number of wash levels	2
Minimum front panel weight in kg	4.0
Maximum front panel weight in kg	11.0
Fascia color	CleanTouch Steel
Construction type	Semi-integrated dishwasher
Product line	ProfiLine
Wash system	Fresh water
Front	Without front
Side panels	Galvanised

## APPLICATION

Suitable for retirement and care homes	•
Suitable for hospitals	•
Suitable for guesthouses	•
Suitable for kindergartens	•
Suitable for universities and schools	•
Suitable for offices	•
Suitable for domestic use	•
Suitable for small businesses	•
Suitable for sports clubs	•

## PERFORMANCE DATA

**Tested virucidal efficacy**

•

**Circulation pump, Qmax in l/min.**

283.9 (75)

**Shortest program duration in minutes**

52

**Maximum final rinse temperature in °C**

180 (82)

**Cleaning performance, place settings/cycle**

13

**Service life in wash cycles**

12500

**CONTROLS****Programs [quantity]**

8

**Check filter indicator**

•

**Control type**

Electronic controls

**Program selection**

Program Selector Buttons

**Max. delay start in h**

24

**Time left display**

•

**Program sequence indicator**

•

**Choice of display language**

•

**STANDARD ELECTRICAL CONNECTION****Electrical connection**

AC 120V 60HZ

**Heater rating in kW**

1.300

**Total rated load in kW**

1.400

**Fuse rating in A**

15

**Length of power cord in m**

5 (1.70)

**NEMA plug: 5–15**

•

**POSSIBLE VOLTAGE VARIANT 1**

<b>Electrical connection</b>	2N AC 120/208-240V, 60HZ
<b>Heater rating in kW</b>	3.500-3.800
<b>Total rated load in kW</b>	3.700-4.000
<b>Fuse rating in A</b>	30

**WATER CONNECTION / DRAINAGE**

<b>Cold or hot water [number]</b>	1
<b>Required flow pressure in bar</b>	0.30-10.00
<b>Drain pump [DN]</b>	22
<b>Maximum drain pump height (delivery head) in cm</b>	39 3/8 (100)
<b>Integrated water softener</b>	•
<b>Maximum water hardness in mmol/l</b>	6.5 (6.50)
<b>Water protection system</b>	Waterproof system
<b>Length of water inlet hose in in. (cm)</b>	59 1/8 (150)
<b>Length of water drain hose in in. (cm)</b>	59 1/8 (150)

**DIMENSIONS AND WEIGHT**

<b>External dimensions, gross height in mm</b>	37 7/8 (960)
<b>External dimensions, gross width in mm</b>	26 1/2 (670)
<b>External dimensions, gross depth in mm</b>	27 5/8 (700)
<b>Gross weight in kg</b>	109 (49)
<b>External dimensions, height in mm</b>	31 3/4 (805)
<b>External dimensions, width in mm</b>	23 5/8 (598)
<b>External dimensions, depth in mm</b>	22 1/2 (570)

<b>Usable space in wash cabinet, height in mm</b>	21 3/8 (540)
<b>Usable space in wash cabinet, width in mm</b>	20 1/8 (510)
<b>Usable space in wash cabinet, depth of upper basket in mm</b>	17 3/4 (450)
<b>Usable space in wash cabinet, depth of lower basket in mm</b>	17 3/4 (450)
<b>Rack height above floor in mm</b>	8 3/8 (210)
<b>Net weight [kg]</b>	93 (42)
<b>Maximum floor load in N</b>	1000

#### EMISSION LEVELS

<b>Sound power level LwA</b>	48.0
<b>Emission sound pressure level at workplace (LpA)</b>	35 dB(A) re 20 µPa

#### PROGRAMS

<b>Universal</b>	•
<b>Short</b>	•
<b>SaniWash</b>	•
<b>Cold / pre-wash</b>	•
<b>Glasses</b>	•
<b>Plastics</b>	•
<b>Energy save / Economy</b>	•
<b>Intensive</b>	•

#### BASKET DESIGN

<b>ExtraComfort baskets</b>	•
<b>Flexible FlexLine Baskets</b>	•

<b>FlexCare glass holder [number]</b>	2
<b>FlexCare cup rack [number]</b>	1
<b>Cutlery basket</b>	•
<b>Height-adjustable upper basket</b>	•
	•

## FEATURES

<b>Commercial-grade electrical connection</b>	•
<b>EcoFeedback</b>	•
<b>Brilliant GlassCare</b>	•
<b>Drying</b>	AutoOpen assisted drying
<b>1 combi dispensing unit in the door for powder cleaning agent and rinsing agent</b>	•
<b>Wash cabinet made of high-quality stainless steel</b>	•
<b>BrilliantLight</b>	•
<b>Child lock</b>	•
<b>Adjustable final rinse temperature</b>	•
<b>Optical interface</b>	•
<b>SmartStart</b>	•
<b>FlexiTimer with EcoStart</b>	•

## TEST CERTIFICATES AND SYMBOLS

<b>EMC radio suppressed</b>	•
<b>CE</b>	•
<b>VDE</b>	•
<b>EN 1717</b>	•
<b>UL</b>	•

**Complies with Machinery Directive 2006/42/EC•**

---

•

---