



COOKTOP FEATURES

Total Burners	6 Italian Aluminum Burners
Front Left	15,000 BTU
Rear Left	9,000 BTU
Front Right	15,000 BTU
Rear Right	9,000 BTU
Front Center	6,000 BTU
Rear Center	9,000 BTU

OVEN FEATURES

Oven Cavity	1
Oven Capacity	5.2 cu. ft.
Bake Element	2800W
Broil Element	3200W
Oven Modes	Broil, Bake, Convection Bake Convection Broil
Cleaning System	SteamClean
Oven Temp Range (F)	150° - 500 °

PRODUCT FEATURES

- **Black Enamel Cooktop:** Durable, easy-to-clean surface for everyday use.
- **Exclusive Continuous Cast Iron Grates:** Smooth pan movement across the cooktop without lifting.
- **Exclusive Zinc Alloy Knobs with Blue Cascade Lighting:** Elegant controls with illuminated accents for a premium look.
- **Single-Spark Ignition with Auto-Reignition:** Reliable ignition system for hassle-free cooking.
- **Italian Aluminum Burners:** Precision burners delivering consistent heat and performance.
- **Exclusive Knurled Stainless-Steel Handle:** Sturdy and stylish design for a comfortable grip.
- **SoftClose Oven Door with Removable Triple-Pane Glass:** Smooth, quiet closing with heat-resistant safety.
- **Single Convection Fan:** Even heat distribution for consistent baking and roasting.
- **Blue Enamel Oven Interior:** Durable, easy-to-maintain finish that withstands high temperatures.
- **Five Rack Positions:** Flexible cooking options for dishes of all sizes.
- **Included Accessories:** Telescopic guides with 2 racks and 1 enamel broiler pan for versatile cooking.

SAFETY FEATURES

- Appliance gas safety device
- Cooktop auto-reignition system
- Child safety lock
- Appliance anti-tip bracket

PRODUCT FEATURES

- Model No.: **VRN3609**
- Product Dimensions: **36"W × 27.375"D × 36"H**
- Package Dimensions: **40.1"W × 32.2"D × 45.6"H**
- Product Weight: **269 lbs**
- Electrical Supply: **240V / 60Hz**
- Electrical Service: **15-amp dedicated circuit**
- Gas Supply: **NG (Natural Gas) / LP conversion kit included**
- Plug: **Molded electrical plug, Type B (NEMA 14-50)**
- Distance to Vent Hood: **30" min / 36" max**
- Gas Connection: **½" gas fitting (bottom right)**



DIMENSIONS & CLEARANCES

Before installing the range, you must locate and secure the included anti-tip bracket to the wall for your range.

The range may be installed flush to the rear wall. You may install a non-combustible material on the rear wall above the range and up to the vent hood. It is not necessary to install non-combustible materials behind the range below the countertop height.

The minimum distance from the side of the range above the countertop to combustible sidewalls must be at least 10 inches.

