# 30" Series 7 Grill, LPG

Series 7

## Stainless Steel | LPG



Designed with flexibility in mind, DCS Grills allow you to cook a wide variety of meals and are engineered to deliver the functionality and power demanded by a professional chef. DCS Grills are hand-finished to perfection to complement the quality of the DCS premium outdoor kitchen and built to withstand the demands of the serious cook and the extremes of mother nature. Available in Natural and LP Gas.

# DIMENSIONS

Height

Width	30 "
Depth	26 5/8 "

# FEATURES & BENEFITS

#### Stainless Steel Burners

The precision ported U-shaped stainless steel burners are rated at a massive 25,000BTU each, offering premium quality and performance. A heat shield directs heat upwards maximizing heating efficiency.

## **Ceramic Radiant Technology**

A layer of ceramic rods provides intense yet even heat. It gives a consistent grilling surface, with controlled heat rather than direct fire.

## **Direct Burner Ignition**

An ergonomic ignition solution, where burners are lit directly from the corresponding knobs.

#### Temperature Gauge - Zero To Sear

Go from zero to sear with DCS Grills' new built-in temperature gauge. It lets you know exactly how hot the grill is, even when the hood is down.

# SPECIFICATIONS

## Accessories (sold separately)

Built-in grill cover	ACBI-30
Insulated jacket	BGB30-IJS (optional)
On cart grill cover	ACC-30
Optional cart mount	CAD1-30 / BGB30-CSS

24 1/4 "

Number of U-burners	
Cooking Surface Area	
Primary cooking area	553 sq
Total cooking area	748 sq
Warming rack area	195 sq
Features	
Full surface searing	
Hood temperature gauge	
Ignition system	Sp
Metal dials	
Warming rack	
Finish	
Material	304 gra stainless st
Weather resistant	
Weather resistant Gas Requirements	
1/2" NPT male with 3/8" in flare adapter	
Gas type	L

1/2" NPT male with 3/8" in flare adapter	•
Gas type	LPG
LP hose with regulator and Type 1 connector	•
Operational pressure	11″ W.C.
Supply pressure	12" to 14" W.C.

DCS

#### QUICK REFERENCE GUIDE > BH1-30-L

#### Installation Dimensions

Cutout depth (proud)	22 3/4 "
Cutout height (proud)	10 1/8 "
Cutout width (proud)	28 1/2 "
Insulated jacket for proud cut-out	Varies - check manual

Performance	
Total Power	50000 BTU
U-burner power	25000 BTU
Power Requirements	
Grill power supply	9V Battery for Ignition

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

#### Other product downloads available at dcsappliances.com

↓ 2D-DWG Grill

SKU

- ↓ 2D-DWG Grill with Insulated Jacket
- 👃 2D-DXF Grill

2D-DXF Grill with Insulated Jacket Installation Guide Grill EN Guide d'installation FR Guía de instalación SP Revit-18 Grill Rhino-5 Grill Rhino-5 Grill Rhino-5 Grill Rhino-5 Grill with Insulated Jacket Rhino-5 Grill with Insulated Jacket Service and Warranty Sketchup-8 Grill Sketchup-8 Grill with Insulated Jacket User Guide Grill EN Guide d'utilisation FR Guía del usuario SP

# A PEACE OF MIND SALE

 $\downarrow$ 

 $\downarrow$ 

 $\overline{\mathbf{1}}$ 

 $\overline{\mathbf{1}}$ 

↓

 $\overline{\uparrow}$ 

 $\frac{1}{2}$ 

 $\overline{\mathbf{1}}$ 

 $\downarrow$ 

 $\mathbf{1}$ 

 $\frac{1}{4}$ 

71640

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com

11125