




The ultra slim design of TT hides quietly within cabinetry and extends less than 2" below the edge. When called to action, the horizontal visor effortlessly pulls out to provide added air capture during cooking. TT design is ideal for smaller kitchens or where under-cabinet space is limited. The 400 CFM blower provides more than adequate power for everyday cooking. The 3 speed blower and LED lighting are operated with modern electronic push button controls, which are out of sight and behind the visor when idle.





	ETT424S1	ETT430SS	ETT436SS
Α	23 1/2"	30''	35 1/3"
В	6 1/9"		
С	11"		
D	1 4/7"		
Е	10 2/7"		
F	18 1/9"	24 1/2"	30"
G		6''	

TT





SPECIFICATIONS

	24" UNIT	30" UNIT	36" UNIT	
Model:	ETT424\$1	ETT430SS	ETT430SS	
Dimensions:	24"W x 17 1/9" D x 11 6/7"H	30" 17 1/9" D x 11 6/7"H	36" 17 1/9" D x 11 6/7"H	
Blower type (internal):	S40am			
Blower performance:				
Speed 1	110 CFM			
Speed 2	190 CFM			
Speed 3	290 CFM			
Boost	400 CFM			
Noise (sones): At working speed	Min: 0.67, Max: 7.46			
Finish:	Stainless Steel			
Controls:	Hidden electronic push controls			
Illumination:	2 LED , 2.1 W			
Filter type:	1 Anodized Dishwasher Safe Aluminum Mesh Filters			
Duct transition:	Round 6" Top Discharge			
Installation type:	Available in recirculating version			
Electrical:	120 V 60 Hz PLUG TYPE B	120 V 60 Hz PLUG TYPE B	120 V 60 Hz PLUG TYPE B	
KITS: Recirculating Kit:	CFC0038668			
CFM Reduction Kit:	KIT02748			
6" round plastic deflector				
WARRANTY:		D LABOR, EARN A 3RD YEAR OF F GISTERING YOUR PRODUCT ON EI		

 $^{^{\}ast\ast}$ For valid warranty extension, register within 3 months from purchase. For USA & Canada Users only

^{*}The product images shown are for illustration purposes only and may not be an exact representation of the product.