



## BSP251610

1 x STS tray-GN2/3-punched-40 mm deep  
1 x STS tray-GN2/3-unpunched-40 mm deep  
1 x grid  
1 x pluggable meat probe

**GN114130:**  
GN insert unperf, st. steel, GN1/3, 40mm

**GN114230:**  
GN insert unperf, st. steel, GN2/3, 40mm

**GN124130:**  
GN insert perf, st. steel, GN1/3, 40mm

**GN124230:**  
GN insert perf, st. steel, GN2/3, 40mm

combi-steam oven 200 series  
24", door hinge: left, Gaggenau Metallic  
**BSP251610**

- Flush installation
- Water tank
- Convection 85 °F to 450 °F (30 °C to 230 °C) can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100% .

### - TFT touch display

### - Steaming without pressure

- Flush installation

### Water tank

Convection 85 °F to 450 °F (30 °C to 230 °C) can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100% .

### TFT touch display

### Steaming without pressure

Electronic temperature control from 30 °C to 230 °C

### Removable meat probe

Net volume (42 litres)

### Cooking modes

Convection + 100 % humidity.

Convection + 80 % humidity.

Convection + 60 % humidity.

Convection + 30 % humidity.

Convection + 0 % humidity.

Dough proofing.

Defrosting.

Regenerating.

Low temperature cooking.

### Operation

Rotary knob and TFT touch display operation.

Clear text display in 44 languages.

Option to save 50 individual recipes (incl. core temperature probe)

Information key with use indicators.

Side-opening door opens up to 110° angle.

### Features

Removable 1.3 litre water tank.

Water level warning.

Meat probe with automatic shut-off function.

Actual temperature display.

Timer functions: cooking time, switch-off time, short-term timer, stopwatch.

Automatic boiling point detection.

48 W halogen light on the side.

Hygienic stainless steel cooking interior.

4 tray levels.

### Safety

Child lock.

Safety shut-off.

Cooled housing with temperature protection.

### Cleaning

Cleaning program.

Drying program.

Descaling programme.

Grease filter, dishwasher-safe.

### Planning notes

Door hinge not reversible.

No other electrical appliances should be installed above the BSP Combi-steam oven.

The door panel front of the appliance extends 13/16" from the cabinet front.

The outer edge of the door handle extends 2 13/16" from the cabinet front.

Consider the overhang, incl. the door handle, when planning to open drawers next to the appliance.

When planning a corner solution, pay attention to the 110° door opening angle.

To achieve the 21 1/16" (550 mm) installation depth, the connection cable needs to follow the slanted edge on the corner of the housing.

The power outlet needs to be planned outside of the niche.

### Rating

Energy efficiency class A.

Total rating 2.1 KW.

Total Amps: 10 A.

208 / 220 - 240 V / 60 Hz.

Electrical cable 59 1/16 without plug (hardwire required).

