Dual Fuel Range, 48", 8 Burners, Self-cleaning

Series 9 | Professional

Stainless Steel with Black Glass | Natural gas




With intuitive touchscreen and specialized cooking functions across two ovens, this range is a stand-out addition to your kitchen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Top burner heat of 23,500 BTU, for seriously fast boiling
- 6.9 cu ft total oven capacity across two oven cavities
- Beautiful LED halo-illuminated dials provide information at a glance

DIMENSIONS

Height	35 ³ / ₄ - 36 ³ / ₄ "
Width	47 ⁷ / ₈ "
Depth	29 ¹ / ₈ "



FEATURES & BENEFITS

Cook with confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

SPECIFICATIONS

FISHER & PAYKEL

Accessories	
Square handle option	AH-R48
Capacity	
Total capacity	6.9cu fi
Cleaning	
Dishwasher proof trivets	
Pyrolytic self-clean	
Controls	
High resolution display	
Metal illuminated dials	
Sabbath mode	
Gas requirements	
Fitting and pipe	½ NPT, min. ⅝" Ø flex
Supply Pressure (natural gas)	6" to 9" W.C
Main oven features	
Bake	
Clean	
Convection Bake	
Convection Broil	

Bake	•
Clean	•
Convection Bake	•
Convection Broil	•
Large broil pan	•
Main oven- Self cleaning	•
Main oven- True convection	•
Number of main oven functions	15

QUICK REFERENCE GUIDE > RDV3-488-N

Oven features

•
•
2
•
•

Oven functions

Pyrolytic self-clean

Oven performance

Main Oven Shelf Positions	5
Main Oven Total Capacity	4.8cu ft
Main Oven Usable Capacity	3.8cu ft
Main oven- Bake	4600W
Main oven- Broil	4000W
Main oven- True convection	2500W
Secondary Oven- Bake	2450W
Secondary Oven- Broil	3600W
Secondary Oven- Capacity	2.1cu ft
Secondary Oven- Capacity	1.8cu ft
Secondary Oven- Shelf	5

Power requirements

Electric circuit	4 wire
Rated current	50A
Supply frequency	60Hz
Supply voltage	120 - 240V

Depth $29 \frac{1}{_8}$ " Depth (Excluding handles) $29 \frac{1}{_8}$ " Height $35 \frac{3}{_4} \cdot 36 \frac{3}{_4}$ " Height (excluding vent trim) $35 \frac{3}{_4} \cdot 36 \frac{3}{_4}$ " Width $47 \frac{7}{_8}$ "

Rangetop features

.

Rangetop reactives	
Sealed Dual Flow Burners™	8
Sealed range top	•
Simmer on all burners	140°F
Vent trim included	Flat vent trim
Rangetop Performance	
Max burner power	23500BTU
Power back centre	18500BTU
Power back centre (2)	18500BTU
Power back left	18500BTU
Power back right	18500BTU
Power front centre	18500BTU
Power front centre (2)	18500BTU
Power front left	23500BTU
Power front right	23500BTU
Total cooktop power	158000BTU

Secondary Oven features

Bake	•
Convection Bake	•
Convection Broil	•
Secondary oven functions	11

W	arranty	
Pa	arts and labor	Limited 2 Years Parts & Labor
SK	υ	81896

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2019.

Date: 21.11.2019 > 2

FISHER & PAYKEL

Product dimensions



24 Hours 7 Days a Week Customer Support T 1300 650 590 W www.fisherpaykel.com