

Specifications

Specification	CL2 S	CL2 M
System Format	2-way	2-way
Frequency Response, On-Wall (-6 dB)	56 Hz - 30 kHz	42 Hz - 30 kHz
Sensitivity (2.83 Vrms @ 1 m, Installed)	84 dB	85.5 dB
Nominal Impedance	6 Ohms	6 Ohms
Minimum Impedance (20 Hz to 20 kHz)	4.9 Ohms	4.8 Ohms
Maximum Peak SPL (AES75, Z-weighted)	108 dB	110 dB
Continuous Power Handling (CTA 426-B)	70 W	100 W
Recommended Amplifier Power (RMS, Music Signal)	150 W	200 W
Bass Alignment	Auxiliary Bass Radiator	Auxiliary Bass Radiator
Crossover Frequency	3.3 kHz	2.6 kHz
Drive Unit Complement	1x 4" C-CAM RST II mid-bass driver 1x 25 mm C-CAM tweeter	1x 6" C-CAM RST II mid-bass driver 1x 25 mm C-CAM tweeter
Available Finishes	Black White	Black White
Included Accessories	Brackets Quick start guide Safety instructions Bolts Torx tool	Brackets Quick start guide Safety instructions Bolts Torx tool
External Dimensions with all accessories fitted (H x W x D)	247 x 140 x 217 mm (9 ^{3/4} x 5 ^{1/2} x 8 ^{9/16} ")	332 x 190 x 240 mm (13 ^{1/16} x 7 ^{1/2} x 9 ^{7/16} ")
Weight (Product, Each)	2.7 kg (5 lb 15 oz)	4.1 kg (9 lb 1 oz)
IP rating	IP66	IP66