

## Ventilator Insert Your Design, Our Power!

18-1/8" Depth, 6" High	MODEL
<ul> <li>◆ 430± CFM @ 2.5 to 7.6 Sones</li> <li>◆ 7" Round Duct</li> <li>◆ Aluminum Mesh Filters</li> </ul>	C2030SD4-SS C2036SD4-SS C2042SD4-SS C2048SD4-SS
<ul> <li>→ 390± CFM @ 2.5 to 7.6 Sones</li> <li>→ 7" Round Duct</li> <li>→ Slim Baffle Filters</li> </ul>	C2030SD4SB-SS C2036SD4SB-SS C2042SD4SB-SS C2048SD4SB-SS
C2000SD4SB is designed to meet the Builder Code of 400 CFMs without a make-up air kit.	

## FEATURES:

- Variable Controls.
- Center Panel Lighting: LED bulbs Included.
- Filters: Aluminum Mesh
- Filters: Slim Baffle
- Electrical: 115 AC, 60 Hz, 9 Amps. For proper installation, unit must be hard wired. Suggested use with 15 Amp Circuit.
- Suggested Distance Code: 30" above cooking surface.

## **OPTIONS:**

- Flange for the perfect fit.
- Remote Wiring.

NO Performance Warranty over BBQ Grill/Griddle.





