

FFAP7033T1

Dehumidifier

Available Colors : White

Large Room 70 Pint Capacity Dehumidifier with Pump

Version : 06/20



Product Specifications

Dehumidifier

Air CFM (High)	182
Air CFM (Low)	159
Bucket Full Indication	Yes
Bucket Style	Front Pull Out
Charge - ozs	7.94
Container Capacity - Pints	13.1
Continuous Drain Operation	Yes
Digital Humidity Readout	Yes
Fan Speed - Fan - General	3
Filter Access	Rear
Filter Check	Yes
Filter Type	Easy-to-Clean Washable Filter
Low Temperature Operation	Yes
Motor RPM (High)	1130
Motor RPM (Low)	930
Noise Level dB (High)	51
Relative Humidity Range Manual	35%-85%

Electrical Specifications

Amps (Cool)	6.7
Horsepower (Cool)	1.00
Plug Type	5-15P
Power Cord Length	6' (6-1/2')
Voltage Rating	115V 60Hz
Watts (Cool)	745

Controls

Auto Shut-Off	Yes
Control Location	Top Center
Control Type	Electronic

Certifications & Approvals

CSA Listed	No
ETL Listed	No
NSF® Certified	No
Safety Certification	UL/CUL
UL Listed	Yes

Dimensions: Exterior

Depth	24-7/16"
Height	15-1/16"
Width	11-9/16"

Performance

Dehumidification -Pints/Day	70
Dehumidification-Liters/Day	33
EEV (Liters per kW-hour)	1.85

General Specifications

PROP 65 Label	Yes
Reconditioned	No
Refrigerant	R410a
Warranty	1 Year Full/5 Year Sealed System

Note: For planning purposes only. Always consult local and national electric, gas and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com / frigidaire.ca. Specifications subject to change. Accessories information available on the web at frigidaire.com / frigidaire.ca

FRIGIDAIRE

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidaire.com
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca