

MIRA TOP

Version
FFMIR16W5FS-R Wall 16" (40
cm) Fasteel – 500 CFM

Collection
Fasteel

EAN code
8034122202297



Photograph is for information purposes only
May not correspond to the selected version

FEATURES

- Scotch brite Fasteel no finger prints
- Perimeter suction
- Electronic control
- LED lighting
- Metallic grease filter, removable and washable
- Optional charcoal filter
- SRS Speed reduction system

Recommended mounting height
from cooking surface to hood
bottom: 24" - 35"

OPTIONAL ACCESSORIES

- FDNUVMTR600**
FDNUVMTR600 - Motor 600
CFM
- FFCHASQC0BL**
FFCHASQC0BL - Square
charcoal filter - Type 3

TECHNICAL FEATURES

- Installation type**
Wall
- Dimensions**
16 / 40 cm
- Finish**
Scotch brite Fasteel no finger prints
- Motor**
500 CFM
- Type of control**
Electronic control
- Speed settings**
4
- Lighting**
Led 2x1,2 W - 3200 K
- Filter**
Metallic filter "Base" - 277x294
mm
- Charcoal filter**
FFCHASQC0BL - Square
charcoal filter - Type 3 (optional)
- Minimum distance**
Gas hob: 24 in
Electric hob: 21 in

PACKAGING:WEIGHTS AND
VOLUMES


- Gross weight**
45 lbs
- Net weight**
36 lbs
- Volumes**
10 ft³
- Packaging size**
Length
40 in
Height
19 in
Depth
24 in

CONSUMPTION AND
CONNECTION FEATURES

- Maximum consumption**
280 W
- Plug type**
Hood comes standard with Nema
5-15P power cord

MOTOR TECHNICAL SHEET

- Maximum capacity**
590 m³/h
I.E.C. 61591
- Maximum noise level**
64 dB(A)re1pW
I.E.C.60704-2-13
- Maximum pressure (Pa)**
500 Pa
- Max. motor power**
203 W



MIRA TOP

Version

FFMIR16W5FS-R Wall 16" (40 cm) Fasteel – 500 CFM

Collection

Fasteel

EAN code

8034122202297

MOTOR TECHNICAL SHEET

Motor Speed	1	2	3	4
Noise level dB(A)re1pW-I.E.C.60704-2-13	45	50	55	64
Capacity (m3/h) I.E.C.61591	230	300	380	590
Maximum pressure (Pa)	390	420	460	500
Motor Power (W)	134	156	180	203
Air outlet	150	150	150	150

CAPACITY / PRESSURE

