

UP48N



Colour range
Body



Blue
grey – BG



Antique
white – AW



White – WH



Blue – MB



Stainless
steel – SS



Graphite
matt – MG



Glossy
black – BK



Burgundy
red – BU



Emerald
green – EG



RAL
Optional RAL – RA

Finishes
Knobs, handles, frames (optional)



Brass – G



Copper – P



Chrome – C



Burnished – B

Optional solid door version
optional +




Order code: add letter "Q" before the "N" letter

Noblesse frames
optional → p. 138

Available ovens

Electric oven	
Primary oven:	Secondary oven:
UOV 80 M	UOV 30 E
Maximum input:	Maximum input:
3.7 kW	2.5 kW

Configurations

5 burners with fry top* and coup de feu	8 burners with fry top*	Induction
		


Electric oven	UP48FSNMP	UP48FNMP	UPI486NMP
	Brass/Copper/Chrome/Burnished	Brass/Copper/Chrome/Burnished	Brass/Copper/Chrome/Burnished

Fuel requirements

Natural gas / Liquid propane	Natural gas / Liquid propane	All electric
Voltage: 240 Volts	Voltage: 240 Volts	Voltage: 240 Volts
Amps: 25.8	Amps: 25.8	Amps: 73.8

**Insufficient amperage may lower heating performance when multiple functions are being used at the same time*

Consumption

 Bridge induction zone Ø 7" 1/4 + Ø 7" 1/4 1.85 / 2.5 kW + 1.85 kW	 Induction zone Ø 5" 3/4 1.4 / 1.8 kW	 Induction zone Ø 7" 1/4 1.85 / 2.5 kW	 Induction zone Ø 8" 11/16 2.3 / 3.2 kW	 Coupe de Feu 5500 btu/h	 Double ring Dual burner 25000 btu/h / 900 btu/h
 Griddle 10500 btu/h / 2000 btu/h + 7000 btu/h / 1400 btu/h	 Oval burner 10500 btu/h / 3100 btu/h	 Big burner 10500 btu/h / 2000 btu/h	 Small burner 7000 btu/h / 1400 btu/h		

Complements & accessories

Hood	UAG48	Hood	UANB48	Ladle holder panel	AM4-120
		Brass/Copper/Chrome/Burnished			

Technical drawing & dimensions

