COREtec° the Original

Product Specifications

COREtec PlusGrande

Style Number	VV662	
Construction	Waterproof Foamed Core	
Edge Profile	Enhanced Painted Bevel	
Nominal Dimensions	9" wide, lengths of 28", 55" and 82"	
	US Units	Metric Units
Actual Product Width	8.97"	23 cm
Actual Product Length	Multiple Lengths 27.55", 55.11" and	Multiple Lengths 70 cm, 140 cm and
	82.67"	210 cm
Wear Layer Thickness	30 mil (0.03")	0.76 mm
Overall Product Thickness	0.59"	15 mm
Core Thickness	0.472"	12 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.118"	3 mm
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	
Packaging		
Area per Box	20.67 sq ft	2 sq m
Pieces per Box	18 pcs	
Weight per Box	63.14 lbs	28.63 kg
Boxes per Pallet	36 boxes	
Colors		
The list of colors below complements the entire	e range of colors available for the current product.	
2033 Grande Aleta Oak	3003 Grande Willis Oak	4011 Grande Goldin Oak
4013 Grande Petronas Oak 5013 Grande Lotte Oak	4029 Grande Ellidy Oak 5016 Grande Empire Oak	5012 Grande Makkah Oak 7012 Grande Marina Oak
8002 Grande Vista Oak		
Performance		
Residual Indentation (ASTM F1914)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Resistance to Light (ASTM F1515)	Passes	
Resistance to Chemicals (ASTM F925)	Passes	
Smoke Density (ASTM E662)	Passes	
Radiant Panel (ASTM E648)	Passes, Class I	
Test Reports ma	y be included or listed by the manufacturing/inventory style	number as opposed to the noted selling style nu
Warranties		
USF Lifetime		
Residential Resilient Limited Warranty - Defects	Wear, Waterproof, Petproof	

Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof

USF 10 Year Medium Commercial

COREtec, manufactured by USFloors | 3580 Corporate Dr. | Dalton, GA 30721 | www.COREtecFloors.com



Certifications

GreenGuard (Certification, Gold, Private Label) Certified



