

# PowerLite® L690SE / L695SE

6,000-Lumen Short Throw 3LCD  
Laser Projector with 4K Enhancement



**This incredibly compact projector delivers larger-than-life images with a short 0.5 – 0.7 throw ratio.**



**Bright, true-to-life images** — 3-chip 3LCD technology and 6,000 lumens of equal color and white brightness<sup>2</sup>

**WUXGA with 4K Enhancement Technology<sup>1</sup>** — accepts 4K content and displays double HD resolution on-screen; enjoy a visibly sharper, more detailed picture even at close viewing distances

**Short throw lens with powerful optical zoom** — with a 0.5 – 0.7 throw ratio and 1.4x optical zoom, achieve large images from a close distance; perfect for projecting onto a floor or from behind a screen

**Large, versatile display options** — easily create a display up to 500" diagonal in 16:10, plus ultra wide 16:6 and 21:9 aspect ratios for enhanced content display and visibility

**Simplified installation** — compact and lightweight design featuring a wide vertical and horizontal lens shift, 1.4x optical zoom, 360-degree mounting, built-in geometric correction tools and a universal VESA mounting pattern

**Low maintenance** — up to 30,000-hour laser light source and air filter<sup>3</sup> in Extended Mode

**Built-in NFC<sup>4</sup>** — reduces installation time of multiple projectors; read and write setting information using the Epson Projector Config Tool app

**Optional attachable PixAlign™ camera** — adds powerful multi-projector tools including screen matching<sup>5</sup>, auto color calibration<sup>5</sup>, blending assist<sup>6</sup> for super wide displays and simple stacking<sup>6</sup> without an external PC

**Over-the-air updates<sup>7</sup>** — allows user to optionally be alerted when a Firmware update is available

**Enhanced connectivity** — HDBaseT® and HDMI® two in and one out for daisy-chaining and signal monitoring

### Specifications

**Projection System** RGB liquid crystal shutter projection system

**Projection Method** Front/rear/ceiling mount

**LCD Size** 0.67" (C-Fine)

**Driving Method** Poly-Silicon TFT Active Matrix

**Pixel Number** 2,304,000 dots (1920 x 1200) x 3

**Native Resolution** WUXGA with 4K Enhancement<sup>1</sup>  
(1920 x 1200 x 2)

**Resolution On-Screen** WUXGA with 4K Enhancement<sup>1</sup>/  
4.6 million pixels

**Resize** 640 x 480, 800 x 600, 1280 x 1024, 1400 x 1050

**Aspect Ratio** Supports 4:3, 16:10, 16:9\*, 16:6\*, 21:9\*

\* With vertical image shift control within letterbox area.

**Pixel Arrangement** Cross stripe

**Color Brightness<sup>2</sup>** Color light output: 6,000 lumens

**White Brightness<sup>2</sup>** White light output: 6,000 lumens

**Contrast Ratio** Up to 5,000,000:1

**Brightness Uniformity (Typical)** 88%

**Color Reproduction** Up to 1.07 billion colors

**Size (Projected Distance)** 100" – 500"

**Projected Distance** 80" screen 1.38 m

**Lens Shift** Vertical: ±50%; Horizontal: ±20%

**Keystone Correction** Vertical: ±30 degrees;  
Horizontal: ±30 degrees

**Light Source** Laser Diode

**Light Source Life<sup>3</sup>** Normal: 20,000 hours; Quiet: 20,000 hours;  
Extended: 30,000 hours

### Projection Lens (Short Throw)

**Type** Optical Zoom (manual)/Focus (manual)/Corner focus (manual)

**F-Number** 1.8 – 2.0

**Focal Length** 7.54 mm – 10.55 mm

**Zoom Ratio** 1.0 – 1.4x (optical)

**Throw Rate Range** 0.5 – 0.7 (optical)

**Lens Cover** Lens cap (without string)

### Other Features

**Operating Temperature** 32 °F to 113 °F (0 °C to 45 °C)

**Power Supply Voltage** 100 V – 240 V ± 10%, 50/60 Hz AC

**Auto Power On** Signal Detection on HDMI/Plug-In Detection (HDMI, USB, BNC)

**Sleep Mode** Yes (with timer)

**HDMI CEC Control** Yes

**Power Consumption**

432 W (Normal Mode)

313 W (Quiet and Extended)

2.4 W (Standby comm on)

0.3 W (Standby comm off)

**Fan Noise** 36 dB (Normal Mode); max. 26 dB (ECO Mode)

**Security** Cable hole, Kensington® lock provision

**A/V Mute** Yes

**Speaker(s)** N/A

**Split Screen<sup>8</sup>** Yes (up to 2 screens)

**Content Playback** Yes

**Quick Corner** Yes

**Arc Correction** Yes

**Edge Blending** Yes

### Interfaces

HDMI (HDCP 2.3) x 2

HDMI Out x 1

HDBaseT x 1

Variable Audio Out: Mini Stereo x 1

USB Connector Type-A x 1

USB Connector Type-B x 1

Serial: RS-232c x 1

Wired LAN RJ45 x 1



L695SE Black



L690SE White

### Other Features (Continued)

**Screen Sharing** Yes

**Corner Wall** Yes

**Curved Surface** Yes

**Camera** Yes

### Effective Scanning Frequency Range (Digital)

**Pixel Clock** 25.1 MHz to 594 MHz

**Horizontal** 26 kHz to 135 kHz

**Vertical** 23.98/24/25/29.97/30/50/59.94/60 Hz

### Dimensions (W x D x H)

**Excluding Feet** 17.32" x 11.97" x 4.80"

**Including Feet** 17.32" x 14.25" x 5.94"

**Weight** 20.5 lb

### Network and Remote Control

**Features** Power, source search selection, A/V Mute, number input, menu, esc, select, Freeze, ID, Customize, E-Zoom, mute, volume, playback control and pointer functions

**Operating Angle** Rear: Right/Left: -55 to +55 degrees; Upper/Lower: +75 to +15 degrees; Front: Right/Left: -30 to +30 degrees; Upper/Lower: 0 to +60 degrees

**Operating Distance** 26 ft (8 m)

**Network Control** PJLink, Crestron Integrated partner, Crestron Connected V2 with Xo Cloud, Extron IP link, Extron XTP, AMX, Control4

### Eco Features

**RoHS** compliant

**End-of-life options available<sup>9</sup>**

Epson America, Inc. is a SmartWay® Transport Partner<sup>10</sup>

Design and Manufacturing centers utilize 100% renewable electricity

Dynamic Contrast (ECO) Mode reduces power consumption by 36%

### Limited Warranty and Service

**Warranty** Three-year limited in the U.S. and Canada

**Service** Whole unit exchange, usually Next-Business-Day

Toll-free telephone support, Monday through Friday

**Epson Connection™**

Pre-Sales Support (United States and Canada): 800-463-7766

Website: [www.epson.com](http://www.epson.com)

### Epson Preferred Plus™ Extended Service Plan<sup>11</sup>

1-Year Next-Business-Day Whole Unit Exchange<sup>12</sup> EPPEXP1

2-Year Next-Business-Day Whole Unit Exchange<sup>12</sup> EPPEXP2

(available for up to a total of 5 years of continuous coverage)

### What's Included

PowerLite L690SE / L695SE projector, power cable, projector remote control with batteries, Quick Setup sheet, cable cover and Quick Setup poster

### Ordering Information & Accessories

PowerLite L690SE (White) V11HB36020

PowerLite L695SE (Black) V11HB36120

Replacement Air Filter (ELPAF65) V13H134AF0

Universal Projector Mount (ELPMBPJG) V12H808001

Custom Micro-Adjustable Projector Mount (ELPMBPRH) V12H809001

Wireless LAN module (ELPAP11) V12H005A02

PowerLite Pilot™ 3R (ELPCB03N) V12H11020

PixiePlus ELPS10

External Speaker (ELPSP02) V12H467020

DC-07 Document Camera V12H759020

DC-13 Document Camera V12H757020

DC-21 Document Camera V12H758020

PixAlign Camera (ELPEC01) V12HA46010

**1** 4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen. **2** Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. **3** No required maintenance for the light source and filter for up to 30,000 hours (Extended Mode) or 20,000 hours (Normal Mode). Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m<sup>3</sup> of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. **4** NFC requires use of a device that includes NFC and may require additional software. **5** Using separate camera for each projector. **6** Requires Epson external camera or built-in camera for each projector and the Epson Projector Professional Tool app. **7** Requires an active Internet connection for alerts and Firmware download. **8** Split Screen feature requires remote control. Consult your user manual for input combinations. **9** For convenient and reasonable recycling options, visit [epson.com/recycle](http://epson.com/recycle). **10** SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. **11** Product comes with a 3-year limited warranty with the option to purchase Extended Service Plans up to a total of 5 years of continuous coverage. Extended Service Plan can be purchased at any time that you are covered under an Epson limited warranty or Epson Extended Service Plan. See individual service plan for details. **12** Expedited shipping not available in all areas. Orders must be placed and processed by 1 p.m. Pacific Time, Monday through Friday, excluding holidays.

See the latest innovations from Epson Business Solutions at [epson.com/forbusiness](http://epson.com/forbusiness)



**Epson America, Inc.**  
3131 Katella Ave., Los Alamitos, CA 90720

Specifications and terms are subject to change without notice. EPSON, the 3LCD logo and PowerLite are registered trademarks and Epson iProjection is a trademark of Seiko Epson Corporation. Epson Connection, Epson Preferred Plus, Pilot and PixAlign are trademarks of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2025 Epson America, Inc. CPD-65489R2 5/25

### Contact: