

# GLXX-HDSW16

## 16 Channel Heavy Duty Switch Module

The GLXX-HDSW16 is a Crestron® Green Light Express® switching module chassis for up to 16 channels of heavy duty power switching. The chassis requires **GLR-HD-1P** (single pole) or **GLR-HD-2P** (double pole) heavy duty relays. The module is part of a complete Crestron engineered GLPX Green Light Express panel.

For more information on Crestron Green Light commercial lighting products, please contact Crestron **Sales Support Services**.

### SPECIFICATIONS

#### Load Ratings

Uses modular relays; Refer to single pole [\(GLR-HD-1P\)](#) or double pole (GLR-HD-2P)

#### Power Requirements

Requires 24 Volts DC, delivered via 16 pin GLXX-CTRL

#### Connectors

(2) 16-pin IDC headers; Connect to adjacent module or GLXX-CTRL using interconnect cable provided

#### Environmental

Temperature: 32° to 104°F (0° to 40°C)  
Humidity: 10% to 90% RH (non-condensing)  
Heat Dissipation: 52 BTU/Hr (fully populated with relays)

#### Electrical Regulatory Certifications

UL508, Section 41 (Endurance Test) and Section 61C (Electronic Ballasts)  
IEC60669-2-1, Section 19.102 (Contact mechanisms incorporated in electronic switches, intended for fluorescent lamp circuits or

# GLXX-HDSW16

## 16 Channel Heavy Duty Switch Module

