



Front Load Perfect Steam™ Electric Dryer with Instant Refresh – 8.0 Cu. Ft.

Dryer

Version: 10/25

Product Specifications

Dryer

Air Flow	200 CFM
Drum Back Type	Painted Steel
Drum Material	Painted Steel
Dryness Level Selections	Yes
Lint Filter	Yes
Moisture Sensor	Yes

Dryer Options

Delay Start Time	1-12 Hours
Dry Boost	Yes
Extended Tumble	Yes
Perfect Steam	Yes
Wrinkle Release	Yes

Dryness Level

Max	Yes
High	Yes
Normal	Yes
Low	Yes
Damp	Yes

Exterior

Door Latch	Yes
Reversible Door	Yes

Electrical Specifications

Minimum Circuit Required	30 Amps
Voltage Rating	208/240v

Installation

Optional Pedestal	Yes
Power Cord Included	Yes
Ventilation Type	Vented

Performance Certifications and Approvals

ENERGY STAR Certified	Yes
-----------------------	-----

Right to Repair Details

Right to Repair	Available - Visit electrolux.ca/en/Owner-Support/right-to-repair for more information
-----------------	---

Dryer Cycles

Cycle Count	7
Bulky	Yes
Delicates	Yes
Fast Dry	Yes
Heavy Duty	Yes
Instant Refresh	Yes
Normal	Yes
Timed Dry Time	Yes

Drying Temperatures

Low	Yes
Normal	Yes
High	Yes
Sanitize	Yes
Eco Dry	Yes

Controls

Cancel	Yes
Control Lock	Yes
Cycle Status Lights	Yes
Delay Start	Yes
Estimated Time Remaining	Yes
Pause Function	Yes
Power On/Off	Yes
Start	Yes

Dimensions and Volume

Height	38"
Width	27"
Depth	32"
Depth With Door 90° Open	53 1/2"
Dryer Drum Capacity	8 Cu. Ft.
Dry Linen Capacity Tested Amount	11.5 kg

Energy Data

Combined Energy Factor (CEF)	3.48
kWh/cycle	2.5 kWh
kWh/year	620 kWh

General Specifications

Chime On / Chime Off	Yes
Leveling Legs	Yes
Prop 65 Label	No
Warranty - Labor	1 Year
Warranty - Parts	1 Year

Safety Certifications and Approvals

UL Listed	Yes
-----------	-----

The diagram illustrates the installation requirements for a freestanding dryer in two configurations: freestanding and stacked.

Freestanding Installation:

- Clearance:** 53.1" (136 cm)* to clear open door.
- Depth:** 32" (81.25 cm)* to front of closed door.
- Height:** 38.0" (96.5 cm) to the top of the unit.
- Base:** freestanding dryer on floor or floor line; dryer mounted on optional pedestal.
- Back Panel:** 27.0" (68.5 cm) wide. Centerline height of rear vent is 3.7" (9.5 cm) from the bottom edge. Gas supply pipe on rear of gas unit is 1.5" (4 cm) from the top edge. Electrical supply on rear of unit is 3.7" (9.5 cm) from the top edge. Centerline height of rear vent is 19.0" (48 cm) from the bottom edge. Distance from centerline of rear vent to the bottom edge is 13.5" (34.5 cm).

Stacked Installation:

- Clearance:** 53.1" (136 cm)* to clear open door.
- Depth:** 32.0" (81.25 cm)* to front of closed door.
- Height:** 75.75" (192.5 cm) to the top of the upper unit.
- Base:** approved stacking kit (STACKIT7X) required for stacked installation.
- Back Panel:** 27.0" (68.5 cm) wide. Centerline height of rear vent is 3.7" (9.5 cm) from the bottom edge. Gas supply pipe on rear of gas unit is 1.5" (4 cm) from the top edge. Electrical supply on rear of unit is 3.7" (9.5 cm) from the top edge. Centerline height of rear vent is 19.0" (48 cm) from the bottom edge. Distance from centerline of rear vent to the bottom edge is 13.5" (34.5 cm).

³ Power supply cord length on washer approximately 60 inches (152.5 cm).