


- The Captur<sup>™</sup> system's advanced blower design features a forward positioned centric inlet to remove smoke and odor faster. Three-speed blower control exhausts at 300 CFM.
- Smooth-flow blower wheel design and high flow filters ensure quiet,
  1.2 sone operation at normal speed.
- Bright, two-level LED modules supported by a 3-year warranty illuminate evenly and are tested in cooking environments to ensure long life without dimming.
- Tap-touch, 3-speed capacitive control features a smooth, easy-to-clean surface.
- Dishwasher-safe, deluxe micro-mesh filters provide highly efficient grease removal and patterned cover provides a decorative complement to the hood design. The filter clean reminder ensures they will always maintain a high level of capture.
- EZ1 brackets make it easy for singleperson installation in less than half the time of traditional methods.
- ADA compliant, remote operation is possible using a standard UL approved wall switch (kit sold separately).
- Non-duct capable with use of charcoal filters, sold separately. Hidden louvers on top of hood exhaust away from cabinetry.



## **SPECIFICATIONS**

## **OPTIONAL ACCESSORIES**

Width	Blower CFM	Normal Sones	Volts	Amps	Duct	Non-Ducted Charcoal Filter	ADA Electronic Adapter Kit*
30"	300	1.2	120	.65	3-1/4" x 10" or 7" RD	HPF30 (Type Xc)	HAWRK3
36"						HPF36 (Type Xd)	

<sup>\*</sup> Kit sold separately.