

Special Notes: LED lights. WBAR warming light bar is available on selected models.

Isometric view of a tapered rectangular block. The dimensions are as follows:

- Height: 18"
- Top width: 12"
- Bottom width: 4"
- Front face labels: NP-24" and NPX-27"
- Bottom edge label: WIDTH

600 CFM B200 Dual Blower (Top View)

The diagram shows a circular blower unit with the following specifications:

- Wall Side:** Indicated by a downward arrow on the left.
- Electrical:** A connection point on the left, with a vertical distance of $1\frac{3}{4}"$ from the centerline.
- Centerline of Hood:** A vertical dashed line passing through the center of the unit.
- Dimensions:**
 - Horizontal distance from the wall to the center: $5\frac{1}{2}"$
 - Horizontal distance from the center to the right edge: $5\frac{1}{4}"$
 - Vertical distance from the centerline to the top vent holes: $5\frac{1}{4}"$
- Vent Holes:** Two small circles located above the centerline.
- 8" Outlet:** The main circular opening of the blower.

Optional Duct Cover

18"

30"

36"

MODEL	VOLTS	AMPS+	HZ	RPM	CFM SP@0.0"	EQUIV CFM\$	CFM SP@0.1"	CFM SP@0.2"	CFM SP@0.3"	MIN. ROUND DUCT SIZE	SONES#
B200 Dual	115	4.0	60	1550	600	900	531	480	430	8" (50 sq. in.)	6.5

Ratings in accordance with the Standard Test Code by the Energy Systems Laboratory of the Texas Engineering Experiment Station.