

PFD 104 SCVi XXL [120V/208-240V]

Fully integrated Full-sizedishwasher with 3D MultiFlex cutlery tray for large loads of dishware in households, offices and utility areas.



- Wash performance: 16 place settings in just 24 min.*
- 13% less energy consumption**
- Door opens automatically after two knocks – Knock2open
- Everything completely dry AutoOpen assisted drying
- Innovative design and maximum convenience 3D MultiFlex Tray

EAN: 4002516366942 / Material number: 11605520 / Old Material Number: 61010405CDN

Construction type and design	
Model	Fully integrated dishwasher
XXL dishwashers	• Tally integrated distiwasher
Range	ProfiLine
Wash system	Fresh water front loader
Number of levels	2
Front	Without front
Side walls	Galvanised
	Obsidian Black
Control panel color	5.0
Minimum front panel weight in lbs	12.0
Maximum front panel weight in lbs	12.0
Application	
Suitable for retirement and care homes	<u> </u>
Suitable for Bed & Breakfast	<u> </u>
Suitable for child care facilities	<u>•</u>
Suitable for universities and schools	<u>•</u>
Suitable for offices	<u>•</u>
Suitable for domestic use	•
Suitable for small businesses	<u> </u>
Suitable for sports clubs	•
Performance data	
Tested virucidal efficacy	•
Certified hygiene	•
Circulation pump, Qmax in gal/min (I/min)	_ 19.8 (75)
Shortest program duration in min.	24
Maximum final rinse temperature in °F (°C)	180 (82)
Cleaning performance, place settings/cycle	16
Service life in wash cycles	12500
Control	
Control system	Electronic controls
Program selection	Program selectors
Max. delay start in h	24
Countdown indicator	•
Programs [quantity]	8
Program sequence indicator	•
Choice of display language	•
Check filter indicator	•
Standard electrical connection	
Electrical connection	2N AC 120/208-240V, 60HZ
Heater rating in kW	3.50-3.80
Total connected load in kW	3.70-4.00
Fuse rating in A	30
Length of power cord in ft (m)	5 (1.70)
NEMA plug: 14-30	•
Possible voltage variant 1	
Electrical connection	AC 120V 60HZ
Heater rating in kW	1.30
Total connected load in kW	1.40
Fuse rating in A	15
÷	

Depending on site conditions (temperature of incoming water / power connection) values given may vary.

[&]quot;Based on the ECO program, compared to the predecessor model."



PFD 104 SCVi XXL [120V/208-240V]

Fully integrated Full-sizedishwasher with 3D MultiFlex cutlery tray for large loads of dishware in households, offices and utility areas.



EAN: 4002516366942 / Material number: 11605520 / Old Material Number: 61010405CDN

Water connection/drainage	
Cold or hot water [number]	1
Required flow pressure in bar	0.30-10.00
Drain hose [DN]	22
Maximum delivery head for drain pump in inches (cm)	39 3/8 (100)
Integrated water softener	•
Maximum water hardness in gpg (mmol/l)	6.5 (6.50)
Water protection system	Waterproof system
Length of water inlet hose in inches (cm)	59 1/8 (150)
Length of water drain hose in inches (cm)	59 1/8 (150)
Dimensions and weight	(100)
External dimensions, net height in inches	33 5/16 (845)
External dimensions, net width in inches	23 9/16 (598)
External dimensions, net depth in inches	21 11/16 (550)
External dimensions, gross height in inches	37 13/16 (960)
External dimensions, gross width in inches	26 7/16 (670)
External dimensions, gross depth in inches	27 9/16 (700)
Usable space in wash cabinet, width in inches (mm)	22 7/8 (580)
Usable space in wash cabinet, width in inches (mm)	20 1/8 (510)
Usable space in wash cabinet, depth of upper basket in	17 3/4 (450)
inches (mm)	
Usable space in wash cabinet, depth of lower basket in inches (mm)	17 3/4 (450)
In-feed height above floor in inches (mm)	8 5/16 (210)
Net weight [kg]	113 (51)
Gross weight in lbs.	128 (58)
Maximum floor loading in N	1000
Emission values	
Emission sound pressure level in workplace (LpA)	33 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	45.0
Programs	
Universal	•
Short	•
SaniWash	•
Cold/Pre-wash	•
Glasses	•
Plastic	•
EnergySave/Economy	•
Intensive	•
Baskets	
Flexible FlexLine basket design	•
FlexCare glass holder [number]	4
FlexCare cup rack [number]	2
Height-adjustable upper basket	•
Patented 3D MultiFlex tray	•
Features	
Commercial-grade electrical connection	•
Drying	Active condensation
	drying, Additional drying, AutoOpen assisted drying
1 Combi dispenser/door for powder and liquid media	•
Wash cabinet made from high-quality stainless steel	•
same made nom mg/r quality stairness stool	



PFD 104 SCVi XXL [120V/208-240V]

Fully integrated Full-sizedishwasher with 3D MultiFlex cutlery tray for large loads of dishware in households, offices and utility areas.