## **30" Industrial Style Induction Range**

800 Series - Stainless Steel HIS8055U





HIS8055U Stainless Steel

The 30" 4 element industrial-style induction range delivers power and performance in a commercial-inspired design.

Features & Benefits
Convection Pro combines a third heating element with a back fan for even browning and time savings by using multiple racks at one time.

Dampened hinges softly guide the QuietClose door shut so the oven door never slams.

Heavy-duty metal knobs have a premium look and feel.

Easy to view, ergonomic tilted display.

Induction cooking is faster and more efficient than gas or electric.

Integrated temperature probe cooks meat to your desired doneness without any guesswork.

Cooking modesBake, Convection Broil, Convection Roast, Pizza, Proof, Convection Roast, Pizza, Proof, Convection Roast, Pizza, Proof Convection Roast, Road Rate / broil element Rate / broil element Rate / broil element Rate / Convection element Rate / Power of back left element watts1,700 / 2,900 W Road	<b>General Properties</b>	
Type of surfaceCeramic GlassKnob materialMetalInterior light1Kitchen timerYesDrawer typeNot availableOven PerformanceIBake / broil element watts1,700 / 2,900 WConvection element watts2,700 WBurner PerformanceITotal induction elements element watts4Power of back left element watts1,400 W (2,200 w/ boost)Power of front left element watts2,300 W (3,700 w/ boost)Power of front right element watts1,850 W (3,000 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts40 AVolts208V / 240VFrequency Fower cord lengthN/APower cord lengthN/APlug type208/240V - 4 prong	Cooking modes	Bake, Broil, Convection Broil, Convection Roast, Pizza, Proof, Convection Multi- rack, Sabbath Mode, Temperature
Knob materialMetalInterior light1Kitchen timerYesDrawer typeNot availableOven Performance1Bake / broil element watts1,700 / 2,900 WConvection element watts2,700 WBurner Performance2,700 WPower of back left element watts4Power of front left element watts2,300 W (3,700 w/ boost)Power of front left element watts2,300 W (3,700 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts1,850 W 	Cleaning type	Catalytic cleaning
Interior light1Kitchen timerYesDrawer typeNot availableOven Performance1,700 / 2,900 WBake / broil element watts1,700 / 2,900 WConvection element watts2,700 WBurner Performance2,700 WTotal induction elements element watts4Power of back left element watts1,400 W (2,200 w/ boost)Power of front left element watts2,300 W (3,700 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Frequency Frequency40 AVolts208V / 240VFrequency Power cord lengthN/APlug type208/240V - 4 prong	Type of surface	Ceramic Glass
Kitchen timerYesNot availableDrawer typeNot availableOven PerformanceBake / broil element watts1,700 / 2,900 WConvection element watts2,700 WBurner Performance2,700 WTotal induction elements element watts4Power of back left element watts1,400 W (2,200 w/ boost)Power of front left element watts2,300 W (3,700 w/ boost)Power of front right element watts2,300 W (3,700 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts40 AVolts208V / 240VFrequency Power cord lengthN/APlug type208/240V - 4 prong	Knob material	Metal
InterventionNotDrawer typeNot availableOven PerformanceIBake / broil element watts1,700 / 2,900 WConvection element watts2,700 WConvection element watts2,700 WBurner PerformanceITotal induction elements element watts4Power of back left element watts1,400 W (2,200 w/ boost)Power of front left element watts2,300 W (3,700 w/ boost)Power of front right element watts2,300 W (3,700 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts40 AVatts8,000 WCircuit breaker Volts40 AVolts208V / 240VFrequency Power cord lengthN/APlug type208/240V - 4 prong	Interior light	1
Oven PerformanceBake / broil element watts1,700 / 2,900 WConvection element watts2,700 WBurner Performance2,700 WTotal induction elements4Power of back left element watts1,400 W (2,200 w/ boost)Power of front left element watts2,300 W (3,700 w/ boost)Power of front right element watts2,300 W (3,700 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts40 AVatts208V / 240VFrequency Power cord lengthN/APlug type208/240V - 4 prong	Kitchen timer	Yes
Bake / broil element watts1,700 / 2,900 WConvection element watts2,700 WBurner PerformanceTotal induction elements4Power of back left element watts1,400 W (2,200 w/ boost)Power of front left element watts2,300 W (3,700 w/ boost)Power of front right element watts2,300 W (3,700 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts40 AVatts8,000 WCircuit breaker40 AVolts208V / 240VFrequency Power cord lengthN/APlug type208/240V - 4 prong	Drawer type	Not available
wattsImage: constraint of the systemConvection element watts2,700 WBurner PerformanceImage: constraint of the systemTotal induction elements4Power of back left element watts1,400 W (2,200 w/ boost)Power of front left element watts2,300 W (3,700 w/ boost)Power of front right element watts2,300 W (3,700 w/ boost)Power of front right element watts1,850 W (3,000 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts40 AVatts208V / 240VFrequency60 HzPower cord lengthN/APlug type208/240V - 4 prong	Oven Performance	
wattsinduction elementsBurner PerformanceTotal induction elements4Power of back left element watts1,400 W (2,200 w/ boost)Power of front left element watts2,300 W (3,700 w/ boost)Power of front right element watts2,300 W (3,700 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts40 AVolts208V / 240VFrequency Power cord length60 HzPower cord length Plug typeN/A		1,700 / 2,900 W
Total induction elements4Power of back left element watts1,400 W (2,200 w/ boost)Power of front left element watts2,300 W (3,700 w/ boost)Power of front right element watts2,300 W (3,700 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts40 AVatts208V / 240VFrequency60 HzPower cord lengthN/APlug type208/240V - 4 prong		2,700 W
Power of back left element watts1,400 W (2,200 w/ boost)Power of front left element watts2,300 W (3,700 w/ boost)Power of front right element watts2,300 W (3,700 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Technical Details1Watts8,000 WCircuit breaker40 AVolts208V / 240VFrequency60 HzPower cord lengthN/APlug type208/240V - 4 prong		
element watts(2,200 w/ boost)Power of front left element watts2,300 W (3,700 w/ boost)Power of front right element watts2,300 W (3,700 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Technical DetailsVoltsVatts8,000 WCircuit breaker40 AVolts208V / 240VFrequency60 HzPower cord lengthN/APlug type208/240V - 4 prong	Burner Performance	
element watts(3,700 w/ boost)Power of front right element watts2,300 W (3,700 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Technical DetailsTechnical DetailsWatts8,000 WCircuit breaker40 AVolts208V / 240VFrequency60 HzPower cord lengthN/APlug type208/240V - 4 prong		4
element watts(3,700 w/ boost)Power of back right element watts1,850 W (3,000 w/ boost)Technical DetailsWatts8,000 WCircuit breaker40 AVolts208V / 240VFrequency60 HzPower cord lengthN/APlug type208/240V - 4 prong	Total induction elements Power of back left	1,400 W
element watts(3,000 w/ boost)Technical DetailsWatts8,000 WCircuit breaker40 AVolts208V / 240VFrequency60 HzPower cord lengthN/APlug type208/240V - 4 prong	Total induction elements Power of back left element watts Power of front left	1,400 W (2,200 w/ boost) 2,300 W
Watts8,000 WCircuit breaker40 AVolts208V / 240VFrequency60 HzPower cord lengthN/APlug type208/240V - 4 prong	Total induction elements Power of back left element watts Power of front left element watts Power of front right	1,400 W (2,200 w/ boost) 2,300 W (3,700 w/ boost) 2,300 W
Circuit breaker40 AVolts208V / 240VFrequency60 HzPower cord lengthN/APlug type208/240V - 4 prong	Total induction elements Power of back left element watts Power of front left element watts Power of front right element watts Power of back right	1,400 W (2,200 w/ boost) 2,300 W (3,700 w/ boost) 2,300 W (3,700 w/ boost) 1,850 W
Volts208V / 240VFrequency60 HzPower cord lengthN/APlug type208/240V - 4 prong	Total induction elements Power of back left element watts Power of front left element watts Power of front right element watts Power of back right element watts	1,400 W (2,200 w/ boost) 2,300 W (3,700 w/ boost) 2,300 W (3,700 w/ boost) 1,850 W
Frequency60 HzPower cord lengthN/APlug type208/240V - 4 prong	Total induction elementsPower of back left element wattsPower of front left element wattsPower of front right element wattsPower of back right element wattsTechnical Details	1,400 W (2,200 w/ boost) 2,300 W (3,700 w/ boost) 2,300 W (3,700 w/ boost) 1,850 W (3,000 w/ boost)
Power cord lengthN/APlug type208/240V - 4 prong	Total induction elementsPower of back left element wattsPower of front left element wattsPower of front right element wattsPower of back right element watts <b>Technical Details</b> Watts	1,400 W (2,200 w/ boost) 2,300 W (3,700 w/ boost) 2,300 W (3,700 w/ boost) 1,850 W (3,000 w/ boost) 8,000 W
Plug type 208/240V - 4 prong	Total induction elements Power of back left element watts Power of front left element watts Power of front right element watts Power of back right element watts Technical Details Watts Circuit breaker	1,400 W (2,200 w/ boost) 2,300 W (3,700 w/ boost) 2,300 W (3,700 w/ boost) 1,850 W (3,000 w/ boost) 8,000 W 40 A
	Total induction elements Power of back left element watts Power of front left element watts Power of front right element watts Power of back right element watts Technical Details Watts Circuit breaker Volts	1,400 W (2,200 w/ boost) 2,300 W (3,700 w/ boost) 2,300 W (3,700 w/ boost) 1,850 W (3,000 w/ boost) 40 A 208V / 240V
Energy source Electric	Total induction elements Power of back left element watts Power of front left element watts Power of front right element watts Power of back right element watts Technical Details Watts Circuit breaker Volts Frequency	1,400 W (2,200 w/ boost) 2,300 W (3,700 w/ boost) 2,300 W (3,700 w/ boost) 1,850 W (3,000 w/ boost) 40 A 208V / 240V 60 Hz
	Total induction elements Power of back left element watts Power of front left element watts Power of front right element watts Power of back right element watts Technical Details Watts Circuit breaker Volts Frequency Power cord length	1,400 W (2,200 w/ boost) 2,300 W (3,700 w/ boost) 2,300 W (3,700 w/ boost) 1,850 W (3,000 w/ boost) 1,850 W (3,000 w/ boost) 8,000 W 40 A 208V / 240V 60 Hz N/A



**Dimensions & Weight Overall** appliance 36" x 29 15/16" x dimensions (HxWxD) 24 15/16" (26 1/2" with bull nose) Required cutout size 36" x 30" x 25" (HxWxD) Adjustable range height 35 9/16" Min. 36 13/16" Max. Oven cavity size 3.9 cu. ft. Overall oven interior 17 3/8" x 24 1/3" x dimensions (HxWxD) 18 3/8" Usable oven interior 17 5/16" x dimensions (HxWxD) 22 13/16" x 17 1/8"

Net weight 212 lbs Accessories-Included

Use and care manual, installation guide, temperature probe, 2 standard racks

Accessories–Optional



HEZ390230 10" AutoChef® pan for 8" and 9" elements



Side Panel Extension Kit Stainless Steel



HEZ9TK30UC 30" Toe Kick Stainless Steel

HEZ9LLUC Metal Pedestal Feet Stainless Steel



Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

© BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.

## **30" Industrial Style Induction Range**

800 Series - Stainless Steel HIS8055U



## **Installation Details**



Accessories: To purchase Bosch accessories, cleaners & parts please visit www.bosch-home.com/us/store or call 1-800-944-2904 (Mon to Fri 5 am to 6 pm PST, Sat 6 am to 3 pm PST). Notes: All height, width and depth dimensions are shown in inches. BSH reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cutout. Warranties: Please see Use & Care manual or Bosch website for statement of limited warranty.

For more information on our entire line of products, go to www.bosch-home.com/us or call 1-800-944-2904

© BSH Home Appliances Corporation. All rights reserved. Bosch is a registered trademark of Robert Bosch GmbH.