

864 TRV 31K Clean Face Deluxe

PREMIUM TRADITIONAL GAS FIREPLACE

FIREPLACE
XTRODINAIR
FIREPLACEX.COM



The 864 TRV31K Clean Face Deluxe in this covered outdoor area features the Herringbone Brick Fireback, and Classic Oak Log Set.

The 864 TRV 31,000 BTU fireplace is perfect for anyone looking to display a big, beautiful fire that provides supplemental year-round heat to spaces up to 1,400 square feet. This top or rear vent (TRV) fireplace is available as a “Clean Face” model with minimal trim, or with one of our beautiful designer faces. The 864 TRV 31K includes the Ember-Fyre® II Burner, Ember-Glo™ ember bed lighting, the CoolSmart TV Wall™ option, and your choice of stunning Classic Oak or Birch Log Sets.

In addition to the great features listed above, both of these Deluxe models include the GreenSmart® Remote Control, 180 CFM convection fan, and adjustable overhead Accent Lights.

864 TRV 31K Clean Face Deluxe

PREMIUM TRADITIONAL GAS FIREPLACE



Features & Options You're Gonna Love

| | |
|----------------------------|----------------|
| Comfort Control™ | YES |
| Burner Type | Ember-Fyre® II |
| Convection Fan | 180 CFM |
| Accent Lights | OVERHEAD |
| Ember-Glo™ | YES |
| Cool Smart TV Wall™ Option | YES |
| Power Exhaust Vent Option | YES |
| Power Heat Duct Option | ONE |

Specifications

| | |
|---|---|
| Height (including standoffs) | 44-3/4" |
| Width | 42-3/4" |
| Depth | 22" |
| Flue Diameter May be reduced. Ask your dealer. | 8" |
| Direct Vent Top Vent | YES |
| Direct Vent Rear Vent | YES |
| Weight | 205 lbs. |
| Glass Viewing Area | 758.8 sq. in. |
| Combustible Min. Mantel Clearances (Measured from base of fireplace to mantle) | 44-3/4" - 48-3/4" |
| Custom Shop Cast Mantel Clearances | See your Authorized Fireplace Xtordinair® dealer for details. |
| Hearth Requirement | None |

Performance

| | |
|---|------------------------|
| Heating Capacity (Up To) | 1,400 Sq. Ft. |
| BTU Input High to Low (NG) | 31,000 - 10,000 |
| BTU Input High to Low (LP) | 31,000 - 8,000 |
| Turndown Ratio | 68% NG 75% LP |
| Canadian EnerGuide P4 Efficiency | 71.48% NG 71.02% LP |
| Steady State Efficiency High (Up to) | 80.38% NG 81.21% LP |
| AFUE (Annual Fuel Utilization Efficiency) | 73.80% NG 73.50% LP |

NOTE: Improper installation of your gas appliance or failure to operate it in accordance to the guidelines detailed in the Owner's Manual may negate your warranty and endanger your home and family. Installation information is available on our website at www.fireplacex.com.

The dimensions and clearances on this page are for reference only!

Refer to the Owner's Manual prior to installation. We recommend all Fireplace Xtordinair® appliances be installed, and maintained on an annual basis by your Specialty Hearth Retailer.

Scan for
Installation Manual



Choose Your Log Set



Classic Oak
10-piece high definition log set



Birch
10-piece high definition log set

Optional Decorative Firebacks

Personalize the inside of your fireplace with one of our many stunning firebacks.




Reversible Common Brick/
Herringbone Brick



Handmade Brick



Black Handmade
Brick



Ledgestone



Old World Stucco



Stacked Tan Brick



Black Glass