Product data sheet

CONSTRUCTION TYPE

Built-in appliance	•
Integrated appliance	•
Door hinging	Right convertible
Convertible hinging	•
Can be installed side by side	•

DESIGN

Lighting BrilliantLight

USER CONVENIENCE

FullAccess EasyClean MaxLoad hinge DynaCool SoftClose SelfClose Push2open Networking with Miele@home •	Freshness system	MasterFresh
MaxLoad hinge DynaCool SoftClose SelfClose Push2open •	FullAccess	•
DynaCool • SoftClose • SelfClose • Push2open •	EasyClean	•
SoftClose • SelfClose • Push2open •	MaxLoad hinge	•
SelfClose • Push2open •	DynaCool	•
Push2open •	SoftClose	•
<u> </u>	SelfClose	•
Networking with Miele@home •	Push2open	•
	Networking with Miele@home	•

CONTROLS

Eco mode •

User interface	MasterSensor
SuperCool	•
Number of temperature zones	2
Sabbath mode	•
FRIDGE / FRIDGE SECTION	
SlidingShelf	•
Door rack for tins	1
Height-adjustable tempered glass shelves	2
Number of vegetable drawers	1
Number of crisper drawers	2
Door rack for bottles	3
EFFICIENCY AND SUSTAINABILITY	
Energy Star	•
SAFETY	
Overflow protection	•
Safety lock	•
Acoustic door alarm	•
Acoustic temperature alarm, freezer section	•
Optical door alarm	•
Optical temperature alarm	•
TECHNICAL DATA	

Customer Service

Replacing lamps

	·
Number of phases	1
Niche width in inches (mm), min.	36 (914)
Niche width in inches (mm), max.	36 (914)
Niche height in inches (mm), min.	84 1/8 (2134)
Niche height in inches (mm), max.	84 1/8 (2134)
Niche depth in mm	24 7/8 (629)
Appliance width in mm	35 3/4 (908)
Appliance height in mm	83 3/4 (2125)
Appliance depth in mm	24 (608)
Weight in lbs (kg)	382 (172.9)
Door hinge technology	Fixed door
Max. weight of door, fridge section, in kg	82 (37)
Total usable capacity in I	20.55 (582) ft³ (I)
Current consumption in milliamps (mA)	4000
Voltage in V	110-120
Fuse rating in A	10
Frequency in Hz	60
Length of power cable in m	11 (3.5)
ACCESSORIES SUPPLIED	
Active AirClean filter	•
APPLIANCE CATEGORY	
Refrigerator	•

AVAILABLE DISPLAY LANGUAGES

Available display languages via Language Options

bahasa malaysia