



# UPS-1000-OL

## TECHNICAL DESCRIPTION

The UPS-1000-OL shall be a two-rack-space or tower on-line UPS unit in a steel and plastic enclosure. It shall operate at 120 volts AC at both 50 or 60Hz and have a 6-foot, grounded, 3-wire #14 line cord. There shall be 6 grounded AC receptacles on the back panel. This unit can accommodate additional battery cabinets to extend it autonomous run time. Overall dimensions shall be 3.39”H x 17.24” or 19.0” (with ears)W x 16.26”D. Weight shall be 37 pounds. The UPS-1000-OL shall have a total load rating of 1,000VA / 9,000 Watts. This unit can accommodate an optional SNMP network card for unit monitoring and shutdown.

SPECIFICATIONS	UPS-1000-OL
Load Rating	8.3A
Voltage Rating	120V
Power Requirement (no load)	0
Under-Voltage Auto Shutdown	Yes
Over-Voltage Auto Shutdown	Yes
Over-Current Auto Shutdown	Circuit Breaker
Over-Temperature Auto Shutdown	Internal temperature fault shutdown
Network Port	Optional SNMP Card
Serial Port	RS-232 on Female 9-pin D-subminiature USB Type B RJ45 on optional SNMP card
Temperature Sensor Input	None
Auxiliary Relay Outputs	With optional relay card
Contact Closure Input	EPO and optional relay card
Dimensions	17.24" W x 16.26" D x 3.39" H
Weight	37 lbs
Temperature Range:	0C to 40C
Humidity Range	< 90% Non-condensing
Agency Listings	UL 1778 CSA-C22.2 No. 107.1

\* 1.2 x 50 microsecond industry standard combination wave surge as per IEEE C62.41

\*\* Specifications subject to change without notice  
SPECS v.030118

