15" Marvel Clear Ice Machine with Arctic White Illuminice™ Lighting

Model # ML15CL & ML15CP

33 ³/₄" H

25 ¹/₂" D including handle

14 ⁷/₈" W

Performance

- The quietest ice machine you can buy
- Energy-saving options conserve water and energy
- Engineered to consistently produce pure, clear ice with unrivaled clarity, immediate cooling and slower melt
- Its uniform size and compact density prove to be the optimal shape to provide faster cooling, while taking up less space in your glass
- Produces up to 39 pounds of clear ice daily, the equivalent of nearly eight convenience-store bags of ice
- Streamlined componentry and single-connection water fitting for simple installation

Storage Capabilities

- Large-capacity bin stores 35 pounds of clear ice, while preserving quality and assuring fresh ice production
- Easy-to-clean, hygienic interior surface

Touchpad Controls

- Marvel Intuit™ Integrated Controls feature all-new settings for ultimate programmability
- Eco Ice™ mode moderates ice production to conservative usage, saving 25% water (91 gallons monthly) and 25% energy ($45 annually)**
- Delay Start/Vacation option automatically postpones operation by 1/4/6/8 (hour or day) intervals, preventing wasteful water use
- Audible alerts and programmed cleaning reminders

Aesthetics

- Illuminice™ feature projects arctic white LED light through clear ice for a dazzling illumination effect
- First-ever glass door model with midnight black interior adds drama to entertaining at home
- Easy-to-install panel-ready option includes soft-close integrated hinge
- Finish options: stainless steel, black or overlay panel

Additional Convenience

- Close Door Assist System™ prevents energy loss by automatically drawing door to a gentle close
- Black toe kick adjustable to 4" with leveling legs
- 1-year parts and labor warranty, 5-year sealed system parts warranty (see owner's guide for details)

**Based on national average of $0.12 kWh at 100% operation
Note: Ice production rate optimal when ambient air and water temperature is at or below 72° F.

Ordering Options

Gravity Drain Applications	
Solid Stainless Steel Door, Right Hinge	ML15CLS2RS
Solid Stainless Steel Door, Left Hinge	ML15CLS2LS
Stainless Frame, Glass Door, Right Hinge	ML15CLG2RS
Stainless Frame, Glass Door, Left Hinge	ML15CLG2LS
Black Door, Right Hinge	ML15CLS2RB
Black Door, Left Hinge	ML15CLS2LB
Panel-Ready Solid Overlay Door, Integrated Right Hinge*	ML15CLP3RP
Panel-Ready Solid Overlay Door, Integrated Left Hinge*	ML15CLP3LP
Factory Installed Pump	
Solid Stainless Door, Right Hinge	ML15CPS2RS
Solid Stainless Door, Left Hinge	ML15CPS2LS
Stainless Frame, Glass Door, Right Hinge	ML15CPG2RS
Stainless Frame, Glass Door, Left Hinge	ML15CPG2LS
Black Door, Right Hinge	ML15CPS2RB
Black Door, Left Hinge	ML15CPS2LB
Panel-Ready Solid Overlay Door, Integrated Right Hinge*	ML15CPP3RP
Panel-Ready Solid Overlay Door, Integrated Left Hinge*	ML15CPP3LP

*Easy installation! No panel kit required. Consult your cabinet maker for overlay panel and handle options.

Finish Options

Solid Stainless Steel

Stainless Steel Frame

Solid Overlay (Panel Ready)*

Black

120518A

Product Dimensions

Rough-In Dimensions

A. Rough-In Width	15"
B. Rough-In Height	34" to 35"
C. Rough-In Depth	24"

Product Dimensions

D. Width		14 7/8"
E. Height		33 3/4" to 34 3/4"
Cabinet Depth		21 1/2"
G. Depth to Front of Door	Solid Door	23 5/8"
	Overlay Door	22 7/8"
H. Depth to Handle		25 1/2" (Stainless Steel)
I. Depth with door at 90°	Solid Door	37 3/8"
	Overlay Door	38 5/8"

Product Features

Interior Cabinet Finish	Black
Capacity	35 lbs of Ice Storage
Shelving System	NA
Shelf Fronts	NA
Other Storage	Ice Bin
Interior Lighting	Illuminice™ LED Lighting
Toe Grill Finish	Black
Hinge	Classic Hinge
Handle	Slim Designer Handle (Panel Overlay Does Not Include Handle)
Control Type	Intuit™
Temperature Range	NA
Lock	No
Electrical Requirements	115V / 60Hz / 15A
Length of Power Cord	6'
Shipping Weight	127 lbs
Finishes	Stainless Steel, Overlay, Black
Vacation Mode	Yes
Agency Approvals	CSA

For comprehensive installation instructions, please visit www.marvelrefrigeration.com to access the owner's guide.

Panel Overlay Dimensions (Solid Door)

Left Hand Hinged Door
15" (38.1 cm) wide appliance

Right Hand Hinged Door
15" (38.1 cm) wide appliance