



Power and Control

Providing the bass channel in your surround sound set up, the award-winning ASW608 offers extraordinary power and control for such a compact subwoofer. Even better, it integrates beautifully with the M-1 satellites, creating a coherent, seamless soundscape. Ultra-solid construction and a Class D amplifier deliver maximum bass precision and minimum deformation.



Technical Specifications

Description	Active closed-box subwoofer system	
Drive unit	1x ø200mm (8 in) paper/Kevlar® cone long-throw	
Frequency range	-6dB at 23Hz and 25/140Hz adjustable (EQ at A)	
Frequency response	±3dB 32Hz – 40/140Hz adjustable (EQ at A)	
Bass Extension	-6dB at 23Hz (position A) -6dB at 28Hz (position B) -6dB at 36Hz (position C)	
Low-pass filter	Active 4th-order, variable cut-off frequency	
Amplifier	Power output:	200W
	Rated power consumption:	40W/ 0.5W standby
	Impedance:	33kΩ
	Signal/noise:	>90dB
	Functions:	Volume level – line in Volume level – speaker in Low-pass filter frequency Low-pass filter bypass (line in only) Bass extension Bass roll-off alignment Auto sense on/standby Phase switch
	Inputs:	Line In (RCA Phono) Speaker in (Binding post) 12v trigger (3.5mm jack)
Dimensions	Height	260mm (10.2 in) no feet
	Width	260mm (10.2 in)
	Depth	330mm (13 in) including grille and controls
Weight	8.85kg (19.5 lb)	
Finishes	Matte Black or Matte White	