New and Improved! Parallel Power Delivery

The RGPC 1200 Custom (available in black or silver) with its beautiful award winning Art Deco design, switchable backlit logo (blue, orange or off), with Six Duplex outlets is perfect for the most demanding AV systems.

To receive the maximum performances install the RGPC 1200 Custom as close as possible to the AV equipment.

The RGPC 1200 Custom utilizes Balanced Surge Protection Design (SPD) to ensure Bidirectional Protection and Reduced Ground Interference.

Features & Benefits

Double - High Current on Demand

Balanced AC Surge Protection

- Resettable Circuit Breaker
- Rack mountable
- Compatible with UL1449 3rd edition for Type 3 locations
- Orange or Blue Illuminated Front - rear switch

Applications

- High End two Channel
- Demanding Home Theaters
- For Crisp and Flawless AV Experience





Specifications

Dimensions (WHD)

Net weight

Mounting

Rack Mountable (w/included detachable ears)

Power Cord (Detachable)

Outlets

Input Voltage

Output Voltage

Frequency

Output Power

Technology AC Surge Protection (type 3 locations)

Efficiency

Cooling

Storage Temperature

Operating Temperature

1200 Custom 120/120

 17×5.25 (w/feet 6.2) x 11

55 lbs

Stand alone Floor / Shelf

6 ft, 12 AWG, NEMA 5-15P

12 (NEMA 5-20R)

120 VAC

120 VAC

60 HZ

12 A (1,440 Watts) Parallel Power Delivery

Balanced

>99%

Convectional

 -40° C to 85° C -40° C to 65° C

1200 Custom 240/240

 17×5.25 (w/feet 6.2) x 11

55 lbs

Stand alone Floor / Shelf

6 ft, 12 AWG, Euro Schuko Plug

8 Euro Shuko 240 VAC 240 VAC

50 HZ

12 A. (2,880Watts)

Parallel Power Delivery

Balanced >99%

Convectional

-40 $^{\circ}$ C to 85 $^{\circ}$ C -40 $^{\circ}$ C to 65 $^{\circ}$ C

