

---

**TABLE 2 - ALTECO C-1 TECHNICAL SPECIFICATIONS**

| ALTECO   | C-1                                   |
|--|---------------------------------------|
| Frequency Range [+/- 3] dB [Hz]                                  | 74 - 26,000                           |
| Sensitivity [2.83V/1m] [dB]                                      | 83.0                                  |
| Nominal Impedance [ohms]   | 6                                     |
| Maximum SPL [dB]   | 103                                   |
| Recommended Amplifier Power [Watt]                               | 40 -100                               |
| Crossover Frequency [Hz]   | 2,100                                 |
| Crossover Principle  | 2-way                                 |
| High Frequency Driver  | 1 x 21 mm soft dome                   |
| Low Frequency/midrange Driver(s)                                 | 1 x 4½"                               |
| Enclosure Type   | Closed                                |
| Bass Reflex Tuning Frequency [Hz]                                | N/A                                   |
| Connection Input(s)  | Single Wire/Spring loaded push-button |
| Recommended Placement  | On speaker/Wall                       |
| Recommended Distance from rear wall to speaker's rear panel [cm] | 1 - 50                                |
| Dimensions (H x W x D) [mm]                                      | 190 x 160 x 255                       |
| Dimensions (H x W x D) [inches]                                  | 7.5 x 6.3 x 10.0                      |
| Weight [kg/lb]   | 2.8 / 6.2                             |
| Accessories  | Rubber feet, manual                   |

All technical specifications are subject to change without notice.