

## SPECIFICATIONS

### INPUTS

Speaker Level Inputs: 3 (6 channels)  
Maximum Input (speaker level): 400W per channel at 4Ω  
Input Impedance: 20kΩ

### OUTPUTS

Preamp Outputs: 3 (6 channels)  
Maximum Output Level: 7.5Vrms  
Output Gain: ±12dB  
Output Impedance: 150Ω

### PERFORMANCE

Total Harmonic Distortion: 0.01%  
Frequency Response: 10Hz-22kHz  
Equalizer Frequencies (front/rear): 125Hz, 250Hz, 500Hz, 1kHz, 2kHz, 8kHz  
Equalizer Frequencies (sub): 31.5Hz, 50Hz, 63Hz, 80Hz, 100Hz

### CONTROL

Remote In  
12VDC Remote Out (always active when unit is on)

### GENERAL

Power Supply: High Headroom PWM Switching  
Current Draw: 350mA  
Recommended Fuse Rating: 2A

### WEIGHTS & DIMENSIONS

Dimensions: 6.0"W x 5.9"D x 1.2"H  
Weight: 3.0lbs (1.4kg)

**IN THE BOX:** LCQ-1, [Speaker](#) and [Power connectors](#), [Manual](#), [Warranty](#)