



Zphono Specifications

Gain at 1 kHz :

MM, 46dB; MC, 61 dB

Input Sensitivity at 1 kHz :

MM, 5 mV in for 1.1 V output

MC, .9 mV in for 1.1 V output

Input Impedance :

MM, 47 k Ω

MC, 100 Ω

Input overload:

MM, 200 mV; MC, 36 mV

RIAA accuracy:

0.25 dB, 20 Hz - 20 kHz

S/N ratio:

MM, 84 dB

MC, 58 dB

Power requirement:

115 V - 230 V, 60/50 Hz, 5 W

Dimensions

9½" width x 1¾" (panel only)

10" depth with connectors

2" height, with feet

241 x 254 x 50mm (44.1mm, without feet)

Rack Mount Accessories - May be Purchased Separately

SBS: Bracket and bolts to attach two Z series units side-by-side in a standard 19" equipment rack.

Zblank: 9½" x 1¾" blank panel, required to mount a single Z series unit; Zblank kit includes one SBS.

Net and Shipping Weight

Net weight: 4 lbs. / 1.8 kg

Shipping weight: 6 lbs. / 2.7 kg



PARASOUND.

Parasound Products, Inc. 950 Battery Street, San Francisco, CA 94111
Customer Service 415-397-7100 / Technical Dept. 415-675-7272 / Fax 415-397-0144
www.parasound.com