QUICK REFERENCE GUIDE > BE1-48C-L Date: 13.02.2025 > 1

# 48" Series 9 Grill, Charcoal, LPG

Series 9

Stainless Steel | LPG



This Series 9 Built in 48" Grill provides the ultimate grilling space for premium outdoor kitchens and will take your grilling experience to the next level.

- Secondary cooking surface allows you to use a wide repertoire of cooking styles and cater for a crowd
- Intuitive lighting with bright in-hood lights and bezel lit control dials
- Easy to lift 90° hood for better access when cooking
- Delivers 25,000 BTU/hr total power per burner allowing you to precisely control heat from 300°F to 1100°F

# DIMENSIONS

Height	27 1/4 "
Width	47 15/16 "
Depth	26 7/8 "

# FEATURES & BENEFITS

# **Easy Lifting Hood**

With extra space under the hood for extra large food items, the hood can be smoothly opened, using one hand, to a full 90° for better access and visibility when cooking.

### Storage For Racks And Tools

The 6" storage accessory extends your grill to fit a 42" or 54" space. It bolts seamlessly onto either side of the grill to store racks, grates and tools. This accessory is sold separately.

# SPECIFICATIONS

## Accessories (sold separately)

6" accessory storage	ASE6-48
Built-in grill cover	ACBI-48E
Griddle plate	BGC-GP TEST
Insulated jacket	BGA48-IJS (optional)
Insulated jacket (with storage accessory unit)	BGA54-IJS (optional)
On cart grill cover	ACC-48E
Optional cart mount	CAD-48E

#### Burners

Number of U-burners	3
Sear burner zone	

#### Cooking Surface Area

Primary cooking area	855 sq.in
Secondary cooking area	738 sq.in
Total cooking area	1593 sq.in

#### **Features**

flat and angled position	Double sided grilling grates
•	Full charcoal burner/smoker
•	Full surface searing
•	Grease management system™
•	Hood temperature gauge
Hot surface	Ignition system
•	Metal dials
2-level racks and tray	Secondary cooking features

#### Finish

Material	304 grade stainless steel
Weather resistant	•

## **Gas Requirements**

1/2" NPT male •



QUICK REFERENCE GUIDE > BE1-48C-L Date: 13.02.2025 > 2

Gas type	LPG
LP hose with regulator and Type 1 connector	•
Operational pressure	11" W.C.
Supply pressure	12" to 14" W.C.
Installation Dimensions	
Cutout depth (proud)	22 3/4 "
Cutout height (proud)	10 1/8 "
Cutout width (proud)	45 3/4 "
Insulated jacket for proud cut-out	Varies - check manual

## Performance

Iotal Power	100000 BTU
U-burner power	25000 BTU

# **Power Requirements**

Supply frequency	60 Hz
Supply voltage	120 V

SKU 71646

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © DCS by Fisher & Paykel Appliances Limited 2020

## Other product downloads available at dcsappliances.com

✓ Installation Guide Grill EN
✓ Guide d'installation FR
✓ Guía de instalación SP
✓ Service and Warranty
✓ User Guide Grill EN
✓ Guide d'utilisation FR
✓ Guía del usuario SP

# A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.dcsappliances.com

